

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP
(Other instruction, see side)
DATE

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME LANGLIE-JAL UNIT
2. NAME OF OPERATOR UNION TEXAS PETROLEUM CORPORATION	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR P.O. BOX 2120, HOUSTON, TEXAS 77252-2120	9. WELL NO. 92
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 660' FEL, UNIT LETTER I	10. FIELD AND POOL, OR WILDCAT LANGLIE-MATTIX (QUEEN) 66
14. PERMIT NO. N/A	11. SEC., T., R., N., OR BLK. AND SUBST OR AREA SEC. 17-25S-37E
15. ELEVATIONS (Show whether BP, RT, GR, etc.) 3110 GR	12. COUNTY OR PARISH LEA
	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	TEMPORARILY

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

GENERAL PROCEDURE

*Note: Please notify BLM(Hobbs)@SOS 393-3612 prior to rigging up.

1. POH W/ROD & PMP, RELEASE TBG ANCHOR & INSTALL BOP.
2. POH W/PRODUCTION STRING.
3. GIH W/CIBP ON PRODUCTION STRING & SET CIBP APPROX. 50' ABOVE TOP PERFS.
4. PRESSURE TEST CASING TO 500 PSIG SURFACE PRESSURE. (SOS)
5. REVERSE CIRCULATE ONE ANNULAR PLUG TBG VOLUME OF INHIBITED* PACKER FLUID.
6. POH W/PRODUCTION TBG & MAKE SURE HOLE IS LOADED W/PACKER FLUID.*
7. REMOVE BOP & INSTALL WELLHEAD W/TAPPED BULL PLUG, NEEDLE VALVE, & PRESSURE GAUGE ADAPTER.

*FLUID SPECIFICATIONS

20 GAL OF UNICHEM TH-606 PER 100 BBL OF FRESH WATER.

RECEIVED
AUG 13 11 39 AM '88
CARLETON
ARREARS
FEE

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE REGULATORY PERMIT COORDINATOR

DATE 08/16/88

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE 9-7-88

*See Instructions on Reverse Side