

Form C-101  
**DUPLICATE**

NEW

ICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

**NOTICE OF INTENTION TO DRILL**

**RECEIVED**

SEP 14 1951

OIL CONSERVATION COMMISSION

HOBBS-OFFICE

9/12/51

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following instructions in Rules and Regulations of the Commission.

Midland, Texas

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Culbertson & Irwin, Inc. Woolworth "C" well No. 1 in SW/4

Company or Operator

Lease

of Sec. 17, T. 25S, R. 37E, N. M., P. M., Langley-Hattix Field, Lee County.

N

The well is 2310 feet (N.) 200 of the south line and 2310 feet (E.) 200 of the west line of Section 17

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_

If patented land the owner is May Woolworth

Address San Angelo, Texas

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is \_\_\_\_\_

Address \_\_\_\_\_

AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: \_\_\_\_\_

Notary to total depth

The status of a bond for this well in conformance with Rule 89 of the General Rules and Regulations of the Commission is as follows: Culbertson & Irwin, Inc. blanket

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
12"	8 5/8	28#	S.H.	250	Cemented to surface	
8"	5 1/2	14#	New	3000	Cemented	2-stage; 400 sack

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3250 feet.

Additional information:

Surface pipe will be set at least 25' in red bed section.  
Oil string will be cemented with 200 sack at shoe and 200 sack through  
2-stage tool at top of salt section.

Approved SEP 14 1951, 19\_\_\_\_  
except as follows:

Sincerely yours,

CULBERTSON & IRWIN, INC.

Company or Operator

By

Position President

Send communications regarding well to:

Name Culbertson & Irwin, Inc.

Address Box 1071, Midland, Texas

OIL CONSERVATION COMMISSION

By

Title Oil & Gas Inspector