

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. Additional instructions in Rules and Regulations of the Commission.

Midland, Texas

1/12/52

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

Culbertson & Irwin, Inc. Woolworth "B" well No. 2 in SE 1/4 of NW 1/4

Company or Operator

Lease

of Sec. 17, T. 25S, R. 37E, N. M., P. M., Langlie-Mattix Field, Lea County.

N

The well is 1980 feet (N) (S) of the north line and 1980 feet (E) (W) of the west line of Section 17.

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_

If patented land the owner is Elizabeth Woolworth

Address San Angelo, Texas

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is \_\_\_\_\_

Address \_\_\_\_\_

AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: \_\_\_\_\_

Rotary to total depth

The status of a bond for this well in conformance with Rule 89 of the General Rules and Regulations of the Commission is as follows: Culbertson & Irwin, Inc. blanket bond

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
12"	8"	28	New	200	Cemented	200 sax
8"	5 1/2"	14	New	2900	Cemented	400 sax*

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 2950 feet.

Additional information: \*200 sax around shoe and 200 sax thru 2-stage tool top of anhydrite. Surface pipe to be set at least 20' in red beds.

JAN 14 1952

Approved \_\_\_\_\_, 19\_\_\_\_

except as follows:

Sincerely yours,

CULBERTSON &amp; IRWIN, INC.

Company or Operator

By

Position President

Send communications regarding well to:

Name Culbertson & Irwin, Inc.Address Box 1071, Midland, Texas

OIL CONSERVATION COMMISSION

By

Title

Oil &amp; Gas Inspector