

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION Drill (OTHER) out Baker packer	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

March 15, 1934
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Klydia C. Winters et al

Humble Oil & Refining Company
(Company or Operator)

Well No. **2** in **F**
(Unit)

SE **NE** **18** **258** **37E** **Cooper-Jal** Pool
(40-acre Subdivision) $\frac{1}{4}$ of Sec. $\frac{1}{4}$ of Sec. T. R. NMPM.,
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Objective: The purpose of this workover is to drill out the Baker packer, clean the well to bottom, treat with 4000 gallons of Dowell Petrofrac, and produce as a open oil well.
Intended Procedure: It is proposed to recomplate the well according to the following procedure: (1) move in and rig up light power rotary rig, (2) kill well with oil and pull tubing, (3) go in hole with bit, drill out Baker Model B-5 production packer set at 3235', and clean well to total depth, (4) pull out of hole and go back in hole open ended with a seating nipple below a backwall packer and hydraulic holddown, (5) set the packer at approximately 3150 feet, (6) treat the open hole section with 4000 gallons of Dowell Petrofrac containing one pound of sand per gallon, (7) scrub well in, test, and place on production.

Well presently producing through perforations in Yates. Yates producing section will be mudded off and shut-off from production by means of a packer.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By *[Signature]*
Title *mb/mb*

Humble Oil & Refining Company
Company or Operator

By *[Signature]*
Position **District Superintendent**
Send Communications regarding well to:

Name **Humble Oil & Refining Company**
Address **Box 2347, Hobbs, N. M.**