MISCELLANEOUS NO			MISCELLANEOUS NO
NEW MEXICO OIL CONSERVATION	111111	HIALL	SANTA FE, NEW MEXICO
		NEV.	MŁXICO OIL CONSERVATION

ate to the Oil Conservation Commission or its proper agent before the work specified is to

NOTICES

Indicate nature of no	tice by checking below:
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	
Ja	1, New Mexico February 16, 1952
OIL CONSERVATION COMMISSION, anta Fe, New Mexico	Nace Date
entlemen:	amihad balam at the
Collowing is a notice of intention to do certain work as de collowing is a notice of intention to do certain work as de collowing is a notice of intention to do certain work as de collowing is a notice of intention to do certain work as de collowing is a notice of intention to do certain work as de certain work as d	
f Sec	
Lea County.	
Ran 3312' 5 1/2" 15.5# J-55 oil string s	OPOSED PLAN OF WORK AND REGULATIONS OF THE COMMISSION et at 3320. Used 600 sacks cement - 300 27. Cement circulated to surface/ Plus
Ran 3312' 5 1/2" 15.5# J-55 oil string s at shoe, 300 thru 2 stage tool set at 11 dewn 11 P M 2-16-52.	AND REGULATIONS OF THE COMMISSION
Ran 3312' 5 1/2" 15.5# J-55 oil string s at shoe, 300 thru 2 stage tool set at 11 down 11 P M 2-16-52. Cement and plugs to be drilled after 11 for 30 minutes to test shut off.	and regulations of the commission et at 3320'. Used 600 sacks coment - 300 27'. Cement circulated to surface/ Plus
Ran 3312' 5 1/2" 15.5# J-55 oil string s at shoe, 300 thru 2 stage tool set at 11 down 11 P M 2-16-52. Cement and plugs to be drilled after 11 for 30 minutes to test shut off.	et at 3320'. Used 600 sacks cement - 30227'. Cement circulated to surface/ Plug PM 2-18-52. 700# will be applied and her Olsen Blount Oil Co. Company or Operator By
Ran 3312' 5 1/2" 15.5# J-55 oil string sat shoe, 300 thru 2 stage tool set at 11 down 11 P M 2-16-52. Cement and plugs to be drilled after 11 for 30 minutes to test shut off. pproved	et at 3320'. Used 600 sacks cement - 30027'. Cement circulated to surface/ Plus PM 2-18-52. 700# will be applied and her Company or Operator By Position Geological Engineer Send communications regarding well to
Ran 3312' 5 1/2" 15.5# J-55 oil string s at shoe, 300 thru 2 stage tool set at 11 dewn 11 P M 2-16-52. Cement and plugs to be drilled after 11 for 30 minutes to test shut off.	et at 3320°. Used 600 sacks cement - 30°27°. Cement circulated to surface/ Plus PM 2-18-52. 700# will be applied and hele Company or Operator By Position Seelegical Engineer Send communications regarding well to Name Olsen Blount Oil Co.
Ran 3312' 5 1/2" 15.5# J-55 oil string sat shoe, 300 thru 2 stage tool set at 11 down 11 P M 2-16-52. Cement and plugs to be drilled after 11 for 30 minutes to test shut off.	ot at 3320'. Used 600 sacks cement - 300 27'. Cement circulated to surface/ Plug PM 2-18-52. 700# will be applied and her Olsen Blount Oil Co. Company or Operator By Position Seelsgical Engineer Send communications regarding well to