

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by a copy of all electrical and radio-activity logs run on well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	940	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	1040	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	2480	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	2620	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	3750	T. Devonian	T. Menefee	T. Madison
T. Queen		T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg		T. Montoya	T. Mancos	T. McCracken
T. San Andres		T. Simpson	T. Gallup	T. Ignacio Qtzite
T. Glorieta		T. McKee	Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	T.
T. Blinberry		T. Gr. Wash	T. Morrison	T.
T. Tubb		T. Granite	T. Todilto	T.
T. Drinkard		T. Delaware Sand	T. Entrada	T.
T. Abo		T. Bone Springs	T. Wingate	T.
T. Wolfcamp		T.	T. Chinle	T.
T. Penn.		T.	T. Permian	T.
T. Cisco (Bough C)		T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from	2620	to	3060	- gas	No. 4, from		to	
No. 2, from	3310	to	3330	- oil	No. 5, from		to	
No. 3, from		to			No. 6, from		to	

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from		to		feet.
No. 2, from		to		feet.
No. 3, from		to		feet.
No. 4, from		to		feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	940	940	red beds, sand				
940	1040	100	anhydrite				
1040	2480	1440	salt & anhydrite				
2480	2620	140	dolomite & anhydrite				
2620	3750	1130	sand & dolomite				
3250	3450	200	sand, dolomite & anhydrite				

RECEIVED

18 1977

CIL CO. COMM. FOR COMM.
HOBBS, N. M.