TEW TEXICO OIL CONSERVATION TOMMTSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the

NOTICE OF INTENTION TO TEST CASING	
CONTRACTOR COST	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
IOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	
	Hobbs, New Mexico 6-14-37
	Place Date
OIL CONSERVATION COMMISSION,	
Santa Fe, New Mexico.	
Gentlemen:	described below at the Anderson-Prichard Oil Cor
Following is a notice of intention to do certain work as Lanehar	described below at the Anderson-Prichard Ull Cor Well No. 1 in C NE NW S
Company or Operator Lease	Weil 140.
Company or Operator of Sec. 21 , T. 25S , R. 37E , N	. M. P. M., Langlie Fiel
Lea. County.	
FULL DETAILS OF I	PROPOSED PLAN OF WORK
TOLLOW INSTRUCTIONS IN THE RU	LES AND REGULATIONS OF THE COMMISSION
FOLLOW INSTRUCTIONS IN THE RO	
rion on 20# APT Conde C Blk. Seamles	ss Casing was cemented at 1245' with 100 sks
a 4 12 27 11 00 PM (100	arations to only intermediate surings of capa
ommon General on $6-13-37$, 11:00 lm. operation $-3/4$ and 13 , to start $6-16-37$. Tests	on casing and cement will be made after
-3/4" and 15", to start 0-10-77. 1080.	
77 * 48.5 m m2.cm	2 OII ORDING CHIM COMMISSION AND
lling this pipe.	OII Cabing and
lling this pipe.	JOHN COLUMN COLUMN TO THE COLU
ittimel compound after drilling	out cement plug the casing must be tested wi
onditional approval after drilling	out cement plug the casing must be tested wi
onditional approval after drilling	out cement plug the casing must be tested wi
onditional approval after drilling	out cement plug the casing must be tested wi
onditional approval after drilling	out cement plug the casing must be tested wired in the presence of a representative of all have been sufficient to reach surface.
onditional approval after drilling	out cement plug the casing must be tested wi ade in the presence of a representative of ald have been sufficient to reach surface.
onditional approval after drilling	out cement plug the casing must be tested wi
onditional approval — after drilling of 000# surface pressure. Test must be model to be a shown to b	out cement plug the casing must be tested winder ade in the presence of a representative of all have been sufficient to reach surface.
onditional approval — after drilling on 000# surface pressure. Test must be maken a shown a common of cement used shown as a common	out cement plug the casing must be tested winded in the presence of a representative of all have been sufficient to reach surface. DUPLICATE Anderson-Prichard Oil Corporation
onditional approval — after drilling on a comparison of the surface pressure. Test must be maked a comparison of the surface. Amount of the comparison of the surface of th	out cement plug the casing must be tested winder ade in the presence of a representative of all have been sufficient to reach surface.
onditional approval — after drilling on a comparison of the surface pressure. Test must be maked a comparison of the surface. Amount of the comparison of the surface of th	out cement plug the casing must be tested wind ade in the presence of a representative of all have been sufficient to reach surface. DUPLICATE Anderson-Prichard Oil Corporation Company or Operator
onditional approval — after drilling on a conditional approval — after drilling on the surface pressure. Test must be maked a conditional approval — after drilling of the surface of the	out cement plug the casing must be tested winder ade in the presence of a representative of all have been sufficient to reach surface. DUPLICATE Anderson-Prichard Oil Corporation Company or Operator By
onditional approval — after drilling on a comparison of the surface pressure. Test must be maked a comparison of the surface. Amount of the comparison of the surface of th	out cement plug the casing must be tested wi ade in the presence of a representative of all have been sufficient to reach surface. DUPLICATE Anderson-Prichard Oil Corporation Company or Operator
onditional approval — after drilling on a comparison of the surface pressure. Test must be maked a comparison of the surface. Amount of the comparison of the surface of th	out cement plug the casing must be tested wi ade in the presence of a representative of all have been sufficient to reach surface. DUPLICATE Anderson-Prichard Oil Corporation Company or Operator
onditional approval — after drilling on 000# surface pressure. Test must be maked and office. Amount of cement used shown approved ** Approved ** except as follows:	out cement plug the casing must be tested wind ade in the presence of a representative of all have been sufficient to reach surface. DUPLICATE Anderson-Prichard Oil Corporation Company or Operator By Position Supt. Send communications regarding well to
onditional approval — after drilling on a comparison of the surface pressure. Test must be maked a comparison of the surface. Amount of the comparison of the surface of th	out cement plug the casing must be tested winder in the presence of a representative of all have been sufficient to reach surface. DUPLICATE Anderson-Prichard Oil Corporation Company or Operator By Position Supt. Send communications regarding well to
Approved Approved 19 except as follows:	out cement plug the casing must be tested wind ade in the presence of a representative of all have been sufficient to reach surface. DUPLICATE Anderson-Prichard Oil Corporation Company or Operator