

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Atlantic Richfield Company	8. Farm or Lease Name B. T. Lanehart
3. Address of Operator P. O. Box 1978, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>2310</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>21</u> TOWNSHIP <u>25-S</u> RANGE <u>37-E</u> NMPM.	10. Field and Pool, or Wildcat Jalmat-Yates
15. Elevation (Show whether DF, RT, GR, etc.) 3071' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Gas production has declined to where this well is no longer economical to produce. We propose to P & A this well as outlined below:

Set 8-5/8" CIBP in 8-5/8" csg at about 2650'.
Load hole w/mud containing 25 sx gel/100 bbls.
Spot 35 sx (100') cement plug on top of CIBP.
Spot 35 sx (100') from 1200-1100' (top of salt at 1165')
Spot 10 sx in top of well.

All casing strings will remain intact. Dry hole marker will be installed and location cleared and levelled in accordance w/NMOCC regulations.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED D. D. Litcher TITLE Dist. Drlg. Supervisor DATE 2-5-73

APPROVED BY Joe D. Ramey TITLE Dist. I. Supv. DATE

CONDITIONS OF APPROVAL, IF ANY: