


APPROVED

3 - 1963

1 - 10/1962

Form 9-331a
(Feb. 1961)Budget Bureau No. 42-R358.4.
Form Approved.

COPY TO

Land Office Las CrucesLease No. 032650 (b)Unit A. B. Coated "C"E. W. STANLEY
DISTRICT ENGINEERUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 2, 1962

Well No. 24 is located 1980 ft. from N line and 990 ft. from E line of sec. 24SE/4, NE/4, Sec. 24 25S 37E NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Justis-Eliezbry, Tubbe-Drinkard Lea New Mexico
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is 3081 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 36#, 9-5/8" casing 8892'. Cemented w/ 345 sks. reg. 50-50
 Pozmix w/ 2% gel & 1/4# floccle/sk. & 100 sks. reg. w/ 2% gel &
 2% CaCl & 1/4# floccle. Cement circulated. WOC 12 hours.
 Tested w/ 1000# for 30 mins., no drop in pressure.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Tidewater Oil CompanyAddress Box 547Hobbs, New MexicoBy A. F. WadeTitle Area Supt.