(Tota	C-102)
(Revised	7/1/52)

NUMBER OF COPIE	S RECEIVES		
51	TRIBUTION		
SANTA FE			
FILE			N
U.S.G.S.			•
LAND OFFICE			
TRANSPORTER	OIL		
	GA3	Í	
PROBATION OFFI	ε		
OPERATOR			

EW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		Notice of Intention to Temporarily Abandon Well		Notice of Intention to Drill Deeper		
NOTICE OF INTENTION TO PLUG WELL		Notice of Intention Notice of Intention to Plug Back to Set Liner				
Notice of Intention to Squeeze		Notice of Intention to Acidize	X	Notice of Intention to Shoot (Nitro)		
DTICE OF INTENTION NOTICE OF INTENTION		Notice of Intention (Other) Sand Oil frac	frac X (OTHER) Dual Compl			

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

(Place)

Hobbs, New Mexico September 19, 1963 (Date)

111

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.

Amerada	Petroleum	Corporatie	n	Ic	ia Wiml	perle	7	Well No.	11 in	L
	(Cot	npany or Operator)				Lesse				(Unit)
NW 1	SW 1/4	of Sec. 24	н. т.	2 5 S	R.	37E	NMPM	Justia	s Blineb ry	Pool
(40-acr	e Subdivision)	01 Dec			,		.,,			

LeaCounty.

FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Kill well with refined oil. Pull 2-3/8" tubing. Perforate 7" OD casing in Stuart and Penrose Zenes, subject to logs from 2906! to 3160!. Run macker and ret, bridge plug. Set bridge plug at approx. 3180' and dump sand on top. Set packer above and swab test. Acidize with 500 gals. acid and sand oil frac with 20,000 gals. crude oil and 20,000# sand with M-2, using ball sealers in stages down 3-1/2" tubing. Test, recover bridge plug and run two strings 2-3/8" tubing with beveled cplgs. and complete as a dual. Produce dry gas from Langlie Mattix zone and oil from Blinebry zone.

Approved, 19, 19	Amerada Petroleum Corporation Company or Operator				
Approved OIL CONSERVATION COMMISSION	Position				
By	NameAmerada Petroleum Corporation				
Title	Address Box 668 - Hobbs, New Mexico				