5 - USGS (Lea County) 1 JIM (Engineer) 1 - Admin. Unit (Midland) 1 - CK (Foreman) 1 - File Form Approved. Form 9-331 Budget Bureau No. 42-R1424 Dec. 1973 UNITED STATES 5. LEASE DEPARTMENT OF THE INTERIOR LC-032650 6. IF INDIAN, ALLOTTEE OR TRIBE NAME GEOLOGICAL SURVEY **/** UNIT AGREEMENT NAME SUNDRY NOTICES AND REPORTS (Do not use this form for proposals to drill or to deepen reservoir. Use Form 9–331–C for such proposals.) 8. FARM OR LEASE NAME A. B. Coates "C" oil gas XXXXX well well 9. WELL NO. HOBBS, NEW MUNICP 10 2. NAME OF OPERATOR 10. FIELD OR WILDCAT NAME Getty Oil Company Justis Fusselman & Justis Blinebry 3. ADDRESS OF OPERATOR 11. SEC., T., R., M., OR BLK. AND SURVEY OR P. O. Box 730 Hobbs, NM 88240 **AREA** 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 Section 24, T-25S, R-37E below.) 1980 FNL-2080 FWL AT SURFACE: 12. COUNTY OR PARISH 13. STATE AT TOP PROD. INTERVAL: NMAT TOTAL DEPTH: 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3088 DF SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) MULTIPLE COMPLETE CHANGE ZONES ABANDON\* (other) Repair packer/tubing leak & acidize 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) The subject well is temporarily shut-in due to either packer leakage or hole in tubing. Rig up pulling unit and install BOP. Pull both strings of sucker rods. 2. Run Dialog to determine condition of tubing. Pull short string, then long string with parallel string anchor. Hydrotest long string back in hole. 5. Acidize Justis Fusselman with 3000 gallons 15% NE acid. 6. 7. Hydrotest short string in hole. 8. Acidize Justis Blinebry with 4500 gallons 15% NE acid. Subsurface Safety Valve: Manu. and Type 18. I hereby gertify that the foregoing is true and correct Area Superintendent August 4, 1981 SIGNED This space for Federal or State office use (Orig. Sgd.) PETER W. CHESTER DATE \_\_\_\_\_ APPROVED BY CONDITIONS OF APPROVAL, IF ANY AUG 1 0 1961

JAMES A. GILLHAM

DISTRICT SUPERVISORE Instructions on Reverse Side