

**OIL CONSERVATION COMMISSION**

**HOBBS, NEW MEXICO**

**January 24, 1964**

**Barry Breining  
Tidewater Oil Company  
Box 249  
Hobbs, New Mexico**

**Re: Retest of  
Coates "C" #11-F  
Section 24-T25S-R37E**

**Dear Mr. Breining:**

**This letter is to confirm our telephone conversation of this date.**

**We recommend that a packer leakage test be conducted upon the above well sometime in June, 1964.**

**We recommend the following procedure for this test.**

- 1. Twenty-four hour shut in period.**
- 2. Run a bottom hole pressure bomb in both zones leaving bomb in zone to be shut in while other zone is flowing at a sufficient rate for adequate drawdown. The flow time should be approximately 24 hours.**
- 3. Shut in flowing zone. After one hour pull bomb from shut in zone and run into flowed zone long enough for a good mark.**
- 4. Pull bomb and change charts.**
- 5. Both zones shut in for 24 hours.**
- 6. Repeat of Steps 2, 3, and 4.**

Please notify this Division of the date of the above release.  
It is requested that you be made to release above text.

Very truly yours,

THE INFORMATION COMMISSION

Mr. J. Edgar Hoover  
Department, United States

12/10/61

Mr. J. Edgar Hoover, Director, Federal Bureau of Investigation  
Washington, D.C. 20535  
Enclosed