

OWWO

COUNTY LEA FIELD Justis STATE NM MN 11733

OPR GETTY OIL CO. MAP

11 Coates, A. B. "C"

Sec 24, T-25-S, R-37-E CO-ORD

1980' FNL, 1650' FWL of Sec

Re-Spd 5-5-71 CLASS OWOF EL 30862

Re-Cmp 5-12-71

FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING			
13 3/8" at 538' w/550 sx			
9 5/8" at 3349' w/1300 sx			
7" at 7099' w/600 sx			

LOGS EL GR RA IND HC A

TD 7100'; PBD 7099'

(Tubb-Drinkard) Perfs 5749-6041' NO NEW POTENTIAL

(Fusselman) Perfs 6793-6898' NO NEW POTENTIAL

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Sealing Service, Inc.

PROP DEPTH 6900' TYPE WO

CONT. DATE

6-21-71 F.R.C. 6-24-71; Opr's Elev. 3086' DF
PD 6900' WO (Tubb-Drinkard & Fusselman;
(Orig. comp. 5-28-58 dual thru (Drinkard)
Perfs 5890-5930' & thru (Fusselman) Perfs
6793-6898', OTD 7100', OPB 7099')
TD 7100'; PBD 7099'; COMPLETE
Perf (Tubb-Drinkard) @ 5749', 5750', 5751',
5752', 5776', 5789', 5793', 5832', 5833',
5854', 5989', 5990', 5991', 5993', 5997',
6006', 6008', 6010', 6011', 6012', 6018',
6023', 6034', 6036', 6038', 6041' w/1 SPI
Acid (5749-6041') 4500 gals (15% NE)
Acid (6793-6898') 2000 gals (15% NE)

6-24-71 COMPLETION REPORTED