

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate  
(Other instructions  
verve aide)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-032650 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

A.B. COATES "C"

9. WELL NO.

13

10. FIELD AND POOL, OR WILDCAT

JUSTIS MONTOKA

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

SEC. 24 T25S R37E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3086' DF

12. COUNTY OR PARISH

LEA

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- MIRU PULLING UNIT, PULL RODS AND PUMP  
PULL PROD. TBG

- TIH w/ 6 1/4" DT, DC3, CLEAN OUT TO 6900'

- TIH w/ 7 PKR SET @ 6845', ACIDIZE PREVIOUSLY ABANDONED  
INTERVAL FROM 6854 - 6898 w/ 1000 GAL 15% NEEF ACID

- RESET PKR @ 6750

- ACIDIZE MONTOKA PERFS. 6810' TO 6898' w/ 3000 GAL 15% NEEF ACID  
IN 3 STAGES USING ROCKSALT TO DIVERT

- RELEASE PKR, TOH

- TIH w/ PRODUCTION EQUIPMENT, PLACE WELL ON PRODUCTION

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AREA SUPERINTENDENT

DATE

AUG 18 1988

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

8-31-88

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side