

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instructions
verse side)TE-
re-Form approved.
Budget Bureau No. 42-R1424.Orig & 4cc: USGS
lcc: File

5. LEASE DESIGNATION AND SERIAL NO.

LC -32650 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

A. B. Coates "C"

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Justis Ellenburger

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 24, T25S, R37E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

GETTY OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 249, HOBBS, NEW MEXICO

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980 FNL, 1980 FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOT OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☒ALTERING CASING ☐ABANDONMENT* ☐(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Killed well with brine water. Recovered Otis dual packer at 7253. Milled over top of Baker Model "D" packer and recovered. Found cement retainer leaking at 7890'. Ran Star Tool 6" OD shoe and cut 21" over CI cement retainer. Ran 6-1/8" bit on Bowen casing scraper. Tagged TD at 7890. Ran Star Tool 5-3/4" OD x 5-1/4" ID Cutrite shoe on 5-3/4" x 30' wash-over pipe. Cut over fish to 7925'. Recovered cement retainer inside of wash pipe. Ran Dresser Atlas 5" OD gun as gauge ring, found TD at 7909'. Perforated with casing MgM, six 3/8" holes at 7906 1/2 to 7907 1/2. Ran packer on 2" tubing. Tubing at 7907, packer at 7881'. Acidized with 250 gals 15% MCA with 1/2 gal. Amoco 211 inhibitor, 50% CB converter. Flushed with brine water. Treated with 500 gals. 15% NE acid with one gal Amoco 211, 1 gal. NE agent. Pulled tubing and set CI cement retainer at 7885'. Squeezed with 75 sacks Incon Class C cement with 8/10 of 1 1/2 D-19 at 900#. Drilled cement from 7820 to 7830'. Tagged up at 7875'. Opened wide open and flowed 2.5 BO in one hour and died. Pumped 60 BO with 10 gals. Champion Sulphurtron #61 in well at 1 BPM. Swabbed and flowed back load. Set long string tubing at 7761', Model D packer set at 7750', seating nipple at 5525', sliding sleeve at 7747', parallel anchor at 7491. Tubing receptacle at 7745'. Tested Ellenburger tubing at 4500#. Ran short (McKee) tubing, testing to 4500#. Spotted inhibited water behind #1 string from Model D back up to bottom of McKee perforations. Closed sleeve and tested OK. Pulled tubing plug. Swabbed in. On 24 hr. potential test Ellenburger flowed 165 BO and 1 BW on 20/64" choke with TP 120#, GOR 739/1. Corr. API gravity 43.0.

18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNED BY:

SIGNED

C. L. Wade

TITLE

Area Superintendent

DATE

10-3-68

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment: data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.