

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M.C. Cons. Division

1625 N. French Dr.

Hobbs, NM 88240

FORM APPROVED
Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Texaco Exploration & Production, Inc.

3. Address and Telephone No.

P. O. Box 3109, Midland, TX 79702

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 24, Township 25-S, Range 37-E
Unit Letter A, 990' FNL, 990' FEL

5. Lease Designation and Serial No.
LC-032650 B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

A.B.Coates "C" #20

9. API Well No.

30-025-11742

10. Field and Pool, or Exploratory Area

Justis Ellenburger

11. County or Parish, State

Lea, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☐ Subsequent Report
☒ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. In 1998 set CIBP 7" @ 7500' cap w/65' Tag @ 7438' spot 75 sx plug 7438'-7000' (Ellenburger, McKee)
2. Displace hole w/MLF, 9.5# brine w/25# gel P/BBL
3. Spot 25 Sx plug 6000'-5900' (Drinkard)
4. Spot 25 Sx plug 5100'-5000' (Blinbry)
5. Spot 25 Sx plug 4700'-4600' (Glorietta)
6. Spot 40 Sx plug 3400'-3250' (9 5/8" shoe) Tag @ 3175'
7. Cut 7" Csg @ 3175' unable to pull or Sqz spot 40 Sx plug 3175'-2935' Tag @ 2900'
8. Cut 7" Csg @ 2500 unable to pull or Sqz spot 40 Sx plug 2500'-2300' (B-Salt) Tag @ 2218'
9. Perf 6 holes @ 1500' unable to Sqz spot 50 Sx plug 1548'-1300' (T-Salt) Tag @ 1269'
10. Perf 6 holes @ 600' unable to Sqz spot 50 Sx plug 652'-400' (13 3/8" shoe) Tag @ 382'
11. Circ Cmt 30'-Surf w/10 Sx. Install dry hole marker. 5/15/01

Approved as to plugging of the well bore.
Lea County under Lease is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Title MANAGER

Date 5/15/01

(This space for Federal or State use)

Approved by (ORIG. SGD.) DAVID R. GLASS

Title

Date

MAY 29 2001

PETROLEUM ENGINEER

*See Instruction on Reverse Side

RECEIVED
2001 MAY 25 AM 9:13
FEDERAL BUREAU OF INVESTIGATION
U.S. DEPARTMENT OF JUSTICE