

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
Getty Oil Company

3. ADDRESS OF OPERATOR
P.O. Box 730 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FNL & 990' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☐

FRACTURE TREAT ☐ ☐

SHOOT OR ACIDIZE ☐ ☐

REPAIR WELL ☐ ☐

PULL OR ALTER CASING ☐ ☐

MULTIPLE COMPLETE ☐ ☐

CHANGE ZONES ☐ ☐

ABANDON* ☐ ☐

(other) Plugback & perforate higher in Ellenburger pay (x)

5. LEASE
LC-032650(b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
A.B. Coates "C"

9. WELL NO.
20

10. FIELD OR WILDCAT NAME
Justis Ellenburger

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
24, 25S-37E

12. COUNTY OR PARISH
Lea

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3079' DF

RECEIVED
MAY 27 1982
(NOTE: Report results of multiple completion or zone change on Form 9-331-C)
OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/13/82 Dresser Titian ran gauge ring to 7690'. Set 4 1/2 CIBP @ 7695'. Perf Ellenburger 2 SPF 7536, 38, 40, 46, 48, 50, 52, 58, 60, 62, 64, 70, 71, 82, 84, 86, 88, 98, 7610, 28, 42, 44, 48, 50, 56, 58, (54 holes). Ran 2 3/8" tbg, 7" pkr. to 7658'.

5/14/82 Titian spot 3 bbls acid over perfs 7536-7658, (54 holes) Ran & set pkr to 7277', tail pipe @ 7405'. Treat w/4000 gals 15% HCL 50 balls flush w/35 bbls 0 pressure, SD. Vac. 413 bbls load, pull pkr, ran 2 3/8" tbg, anchor @ 7498'. SN. 7692. Place well back on production.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Donald P. Crockett Title Area Superintendent DATE May 20, 1982

ACCEPTED FOR RECORD
PETER W. CHESTER
AUG 10 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

APPROVED BY _____ DATE _____
CONDITIONS OF APPROVAL IF ANY: _____
TITLE _____ DATE _____

*See Instructions on Reverse Side

RECEIVED

AUG 11 1982

G.ED.
HOBBS OFFICE