

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032650 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

A. B. Cantos "B"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Justis Pecosman

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

24, 25E, 37E

12. COUNTY OR PARISH

Lee

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

GENTRY OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 249, BURNS, NEW MEXICO

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL, 1650' FWL, Sec 24

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3079 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☒

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Milled Baker Model D packer loose and pushed to 6838'. Run bit and casing scraper to 6838'. Set HESCO cement retainer at 6801'. While testing tubing, retainer slipped down hole to 6806'. Milled retainer loose and pushed to 6827'. Set HPS at 6576'. Squeamed with 30 sacks Class II cement with 4% floccs per sack and .5 of 1% CFB-2. Tagged top of cement at 6701'. Mixed 19 bbls gelled brine w/400# buttons and 400# wide range Gelbeads. Spotted across Brinkard perforations. Squeamed into perforations. Ran 6-1/4" bit and drilled cement from 6701 to 6790' HHD. Ran collar log. Perforated from 6730-32 with two shots/ft; two shots at 6740.5'; two shots per ft. from 6751-57; and 6760-75'. Set HPS at 6653', tubing at 6778'. Treated perforations with 1500 gals 15% mud acid. Maximum pressure 2400#. Average rate 1 MBL. Stabbed and flowed back load. Palled packer. Ran Model D packer and set at 6690'. Parallel anchor at 5946'. Riggled up both strings in tension.

18. I hereby certify that the foregoing is true and correct

ORIGINAL SIGNED BY:

SIGNED C. L. Wade

TITLE Area Superintendent

DATE 3-6-69

(This space for Federal or State office use)

APPROVED

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

J. L. GORDON
DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.