

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Orig⁸cc: CCC, Hobbs
cc: Regional Office
cc: file

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator SINCLAIR OIL & GAS COMPANY	8. Farm or Lease Name Vimberly LN
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico 88240	9. Well No. 3
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>24</u> TOWNSHIP <u>25S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat Justis Tubb Drinkard Justis Fusselman
15. Elevation (Show whether DF, RT, GR, etc.) 3085.4 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	
Squeeze Justis Tubb Dri. and Justis <u>y</u> OTHER <u>Fusselman, reperforate Fusselman & acidize.</u>	

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

PROPOSE TO: Squeeze w/cement below Model "D" packer @ 6980' Justis Fusselman perforations 7014-7058'. Test squeeze. Set retainer @ approx. 5850' and squeeze Drinkard perforations 5906-5944' w/cement. Drill out to approx. 6980' and test squeeze. Perforate 7"OD casing opposite Fusselman @ approx. 6847,49,52,60,66,67, 73,74, 6902,03,04,6941,42'. Acidize w/approx. 1,000 gals. acid, swab back load, test and complete as single zone oilwell.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Superintendent DATE 4-6-68
APPROVED BY [Signature] TITLE SEAL DATE
CONDITIONS OF APPROVAL, IF ANY: