

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
 Orig & 2cc: OCC, Hobbs
 cc: Regional Office
 cc: file

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

HOBBS OFFICE O. C. G.
 JUL 1 3 38 PM '68

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Winberly WN
9. Well No. 5
10. Field and Pool, or Wildcat Justis Bli. & Montoya
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator SINCLAIR OIL & GAS COMPANY
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER C 990 FEET FROM THE North LINE AND 2310 FEET FROM THE West LINE, SECTION 24 TOWNSHIP 25S RANGE 37E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3077.6' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Squeeze Montoya, perf. Fusselman, acidize and dual complete, w/present Bli.

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD Drilled 8210', PBTD 6825'. Presently completed in Justis Montoya perf. 6802-6822' and Justis Blinebry 5391-5483'.

PROPOSE TO: Squeeze cement Montoya below retainer @ 6,720' thru perfs. 6802-6822'. Perforate Fusselman w/2-3/8" jets per. ft. at approx. 6647-48, 6651-54 and 6663-68'. Acidize w/approx. 1000 gals. breakdown acid. Complete in Justis Montoya and Present Justis Blinebry as dual oil - oil-well.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Superintendent DATE 7-1-68
 APPROVED BY [Signature] TITLE Supervisor DATE 7-1-68
 CONDITIONS OF APPROVAL, IF ANY: