

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE*

(See other
instructions on
reverse side)Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other _____				5. LEASE DESIGNATION AND SERIAL NO. NM 0766																									
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other _____				6. IF INDIAN, ALLOTTEE OR TRIBE NAME																									
2. NAME OF OPERATOR Union Texas Petroleum Corporation				7. UNIT AGREEMENT NAME																									
3. ADDRESS OF OPERATOR 1300 Wilco Building, Midland, Texas				8. FARM OR LEASE NAME Carlson "A"																									
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 2310' FSL & 2310' FEL At top prod. interval reported below At total depth Same				9. WELL NO. 1																									
14. PERMIT NO. _____ DATE ISSUED May 22, 1974				10. FIELD AND POOL, OR WILDCAT Blinebry																									
15. DATE SPUDDED 2-20-59 16. DATE T.D. REACHED 3-26-59 17. DATE COMPL. (Ready to prod.) This plug back 8-26-74 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 3065' GL 19. ELEV. CASINGHEAD -----				11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 25, T-25-S, R-37-E																									
20. TOTAL DEPTH, MD & TVD 6,954' 21. PLUG, BACK T.D., MD & TVD 6,200' 22. IF MULTIPLE COMPL., HOW MANY* ----- 23. INTERVALS DRILLED BY ----- ROTARY TOOLS 0-6,954 CABLE TOOLS -----				12. COUNTY OR PARISH Lea																									
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 5236-5395 Blinebry				13. STATE New Mexico																									
26. TYPE ELECTRIC AND OTHER LOGS RUN Well was not logged this Plug Back				25. WAS DIRECTIONAL SURVEY MADE No																									
27. WAS WELL CORED No																													
28. CASING RECORD (Report all strings set in well)																													
<table border="1" style="width:100%"><thead><tr><th>CASING SIZE</th><th>WEIGHT, LB./FT.</th><th>DEPTH SET (MD)</th><th>HOLE SIZE</th><th>CEMENTING RECORD</th><th>AMOUNT PULLED</th></tr></thead><tbody><tr><td>13 3/8"</td><td>48#</td><td>573'</td><td>17 1/2"</td><td>450 SX.</td><td>NA.</td></tr><tr><td>9 5/8"</td><td>36 & 40#</td><td>3,273'</td><td>12 1/4"</td><td>1,400 SX.</td><td>NA.</td></tr><tr><td>7"</td><td>20, 23, & 26#</td><td>6,953'</td><td>NA.</td><td>200 SX.</td><td>NA.</td></tr></tbody></table>						CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED	13 3/8"	48#	573'	17 1/2"	450 SX.	NA.	9 5/8"	36 & 40#	3,273'	12 1/4"	1,400 SX.	NA.	7"	20, 23, & 26#	6,953'	NA.	200 SX.	NA.
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED																								
13 3/8"	48#	573'	17 1/2"	450 SX.	NA.																								
9 5/8"	36 & 40#	3,273'	12 1/4"	1,400 SX.	NA.																								
7"	20, 23, & 26#	6,953'	NA.	200 SX.	NA.																								
29. LINER RECORD																													
<table border="1" style="width:100%"><thead><tr><th>SIZE</th><th>TOP (MD)</th><th>BOTTOM (MD)</th><th>SACKS CEMENT*</th><th>SCREEN (MD)</th></tr></thead><tbody><tr><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>						SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)																			
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)																									
30. TUBING RECORD																													
<table border="1" style="width:100%"><thead><tr><th>SIZE</th><th>DEPTH SET (MD)</th><th>CATCHER SET (MD)</th></tr></thead><tbody><tr><td>2 7/8</td><td>5,297'</td><td>5,245'</td></tr></tbody></table>						SIZE	DEPTH SET (MD)	CATCHER SET (MD)	2 7/8	5,297'	5,245'																		
SIZE	DEPTH SET (MD)	CATCHER SET (MD)																											
2 7/8	5,297'	5,245'																											
31. PERFORATION RECORD (Interval, size and number)																													
1 JSPF 5236-41'; 5249-56'; 5265-69'; 5271-73'; 5295-98'; 5317-19'; 5321-25'; 5342-45'; 5381-85'; 5393-95'; (Total 46 holes)																													
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.																													
<table border="1" style="width:100%"><thead><tr><th>DEPTH INTERVAL (MD)</th><th>AMOUNT AND KIND OF MATERIAL USED</th></tr></thead><tbody><tr><td>5236-5395</td><td>Acidized w/2000 gals. DS-30 acid</td></tr><tr><td>5236-5395</td><td>Sand Frac. w/80,000 gals.</td></tr><tr><td></td><td>Gelled 9# BW, 120,000# 20/40 sand.</td></tr></tbody></table>						DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED	5236-5395	Acidized w/2000 gals. DS-30 acid	5236-5395	Sand Frac. w/80,000 gals.		Gelled 9# BW, 120,000# 20/40 sand.																
DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED																												
5236-5395	Acidized w/2000 gals. DS-30 acid																												
5236-5395	Sand Frac. w/80,000 gals.																												
	Gelled 9# BW, 120,000# 20/40 sand.																												
33. PRODUCTION																													
<table border="1" style="width:100%"><thead><tr><th>DATE FIRST PRODUCTION</th><th>PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)</th><th>WELL STATUS (Producing or shut-in)</th></tr></thead><tbody><tr><td>9-2-74</td><td>Pumping</td><td>Producing</td></tr></tbody></table>						DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)	WELL STATUS (Producing or shut-in)	9-2-74	Pumping	Producing																		
DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)	WELL STATUS (Producing or shut-in)																											
9-2-74	Pumping	Producing																											
<table border="1" style="width:100%"><thead><tr><th>DATE OF TEST</th><th>HOURS TESTED</th><th>CHOKE SIZE</th><th>PROD'N. FOR TEST PERIOD</th><th>OIL—BBL.</th><th>GAS—MCF.</th><th>WATER—BBL.</th><th>GAS-OIL RATIO</th></tr></thead><tbody><tr><td>9-4-74</td><td>24</td><td>---</td><td>---</td><td>197</td><td>1,000</td><td>50</td><td>5,076</td></tr></tbody></table>						DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	9-4-74	24	---	---	197	1,000	50	5,076								
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO																						
9-4-74	24	---	---	197	1,000	50	5,076																						
<table border="1" style="width:100%"><thead><tr><th>FLOW. TUBING PRESS.</th><th>CASING PRESSURE</th><th>CALCULATED 24-HOUR RATE</th><th>OIL—BBL.</th><th>GAS—MCF.</th><th>WATER—BBL.</th><th>OIL GRAVITY-API (CORR.)</th></tr></thead><tbody><tr><td>---</td><td>---</td><td>---</td><td>197</td><td>1,000</td><td>50</td><td>39.1</td></tr></tbody></table>						FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	---	---	---	197	1,000	50	39.1										
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)																							
---	---	---	197	1,000	50	39.1																							
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Sold																													
35. LIST OF ATTACHMENTS None																													
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records																													
SIGNED <u>tanley A. Post</u> TITLE <u>Gas Measurement Analyst</u> DATE <u>9-5-74</u>																													

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES: SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES				38. GEOLOGIC MARKERS	
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP MEAS. DEPTH TRUE VERT. DEPTH
Caliche	0	240'		Yates	2,295
Red Bed	240'	1,500'		Glorietta	4,607
Anhy & Gyp	1,500'	1,650'		Blaine	5,236
Anhy, Gyp & Salt	1,650'	2,107'		Tubb	5,617
Lime & Gyp	2,107'	3,276'		Drinkard	5,850
Lime	3,276'	3,900'		Fusselman	6,785
Lime & Sand	3,900'	4,010'			
Lime	4,010'	6,900'			
Dolomite & Chert	6,900'	6,954'			
(This Plug Back)					
Blaine	5,236'	5,395'	Tested 221 Bbls oil and 54 Bbls wtr. in 24 hrs following stimulation		