

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

OCT 10 10 16 AM '63

returned to the school on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER Sand oil frac)	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)October 9, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the:

Amerada Petroleum Corporation **Ida Wimberley** Well No. **5** in **C**
(Company or Operator) (Unit)
NE $\frac{1}{4}$ **NW** $\frac{1}{4}$ of Sec. **25**, T. **25S**, R. **37E**, NMPM., **Justis** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Kill well with refined oil. Pull tubing, rerun with retrievable bridge plug, set at 5600' with sand on top. Squeeze Blinebry zone perfs. from 5134' to 5553' with Inconer Latex cement. Drill out and test with 2000#. Lower bridge plug and set at 6000' with sand on top. Sand oil frac Brinkard zone 7" casing perfs. from 5860' to 5914' with 20,000 gals. crude oil, 20,000# 20-40 sand with 1/20th lb. Adomite Mark II, 1000 gals. retarded acid, 300# scale control, 110 gals. Kentel 147 for corrosion, 10 gals. emulsion breaker and 216 ball sealers down 3-1/2" tubing in stages. Shab test, rerun production equipment, resume producing as a dual well from Brinkard and Fusselman zones.

Approved....., 19.....
Except as follows:

Amerada Petroleum Corporation
Company or Operator
By.....

Position..... **District Superintendent**
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Name..... **Amerada Petroleum Corporation**
Address..... **Box 66P Hobbs, New Mexico**