DISTRIBUTION SANTA FE FILE U.S.G.S. LANC OFFICE OPERATOR APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Type of Work DEEPEN DEEPEN PLUG BACK FITTEL OF Lease STATE FOR WILL OTHER S. W. D. SINGLE TAG Will Mystement Name Formation AMULTIPLE TAG Will Mount of Cherotor Andread Heas Corporation Drawer D, Monument, New Mexico Back A, Location of Well OTHER D LOCATED DOCATED 19. Perposeed Depth 19. Perposeed Depth LINE Lea 11. Lievations (Show whether DL, RT, etc.) 21. Lievations (Show whether DL, RT, etc.) 22. Approx. Date Work will start 23. Approx. Date Work will start 23. Approx. Date Work will start 24. 180 San Andres 22. Approx. Date Work will start 2-14-77							
SAME OF STATE SAME CONTINUES SAME OF COMMENT STATE OF PERMIT TO DRILL, DEEPEN, OR PLUG BACK SAME OF COMMENT	NO. OF COPICS RECEIVED	, 	MEXICO OIL CONSER	Form C-101			
Size of Hole Size of Casing Weight Per Foot Setting Center Process of Size of Hole Size of Casing Weight Per Foot Setting Center Process of Size of Hole Size of Casing Weight Per Foot Setting Center on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, set bridge plug at 5500' with 50' of cement on top of plug, thereby plugging off pug. Set processes and Andres zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 4180', acidize with 4500 gsl. No set processes and address zone fr. approx. 4088' to 41	T	198.25	ALSO MEATON OIL CONSERVATION COMMISSION				
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK Tops of Well DRILL DEEPEN PLUG BACK DEEPEN DRILL DEEPEN PLUG BACK DRILL DRILL DEEPEN PLUG BACK DRILL DRI		-	-		ſ		
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUS BACK A. Type of West Drive of West Drive Driv					ĺ		
APPLICATION FOR PERMIT TO DRILL DEEPEN, OR PLUG BACK To be the Agreement Name To the Agre		+				5. State Oil & (Gas Lease No.
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 1. There of Words 1. There of Words 1. There of Words 1. And 1.					1		······································
DEPEN DELT DEPEN DELT DEPEN DELT DEPEN DELT DELT DELT DELT DELT DELT DELT DELT							
DEPEN DELT DEPEN DELT DEPEN DELT DEPEN DELT DELT DELT DELT DELT DELT DELT DELT	APPLICATIO	N FOR PERMIT TO	DRILL, DEEPEN, O	R PLUG BACK			MINITED TO THE STATE OF THE STA
Drawer D. Monument, New Mexico 88265 A. Adense of Granter Drawer D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Monument, New Mexico 88265 A. Continue of the boll our certise D. Continue Our certise D. Continue Our certise D. Continue Our certise D. Continue D. C	la. Type of Work					7. Unit Agreem	ent Name
Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug set bridge plug at 5800' with 50' of cement on top of plug set bridge plug at 5800' with 50' of cement on top of plug set bridge plug at 5800' with 50	DRILL [DEEPEN	PLUG B	ACK X	Perry or Lea	ea Name
Americal Characterist Americal Rese Corporation Americal Rese Corporation Americal Rese Corporation An invented Characterist Drawer D, Monument, New Mexico 88265 Brawer D, Monument, New Mexico 88265 A invented Characterist Drawer D, Monument, New Mexico 88265 A invented Characterist Drawer D, Monument, New Mexico 88265 A invented Characterist Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D Drawer D, Monument, New Mexico 88265 A invented Characterist D D Locare D, Monument, New Mexico 88265 A invented Characterist D D Locare D, Monument, New Mexico 88265 A invented Characterist D D Locare D, Monument, New Mexico 88265 A invented Characterist D D Locare D, Monument, New Mexico 88265 A invented Characterist D D Locare D, Monument, New Mexico 88265 A invented Characterist D D Locare D, Monument, New Mexico 88265 A invented Characterist D D Locare D, Monument, New Mexico 88265 A invented Characterist D D Locare D, Monument, New Mexico 88265 A invented Characterist D D Locare	b. Type of Well		_	MILT	JELE [
Antenna of Characte Antenna of Character Antenna of Character Drawer D, Monument, New Mexico 88265 Justis Fusselman 10, Field and Pool, or Wildert Justis Fusselman 990 ***Extraction of Submitter D Location & Good Pool Pool Pool Pool Pool Pool Pool P	OIL GAS WELL WELL	OTHER S. W.	D	ZONE	ZONE.		errey
Drawer D. Monument, New Mexico 88265 1. Cocarton of New York Control of North Country Country Living D. Locarton 660 retrieon the North Line North Line 1. Cocarton of North	2. Mame of Operator		•			7	
Drawer D. Monument, New Mexico 88265 1. Cocarton of New York Control of North Country Country Living D. Locarton 660 retrieon the North Line North Line 1. Cocarton of North	Amerada Hess	Corporation				10. Field and	Pool, or Wildcat
Drawer D. Monument, New Hearto Social Processing County Description of the County Description Description of the County Description	3. Address of Operator					!	
Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off rusself plugging off plug at 5800' with 50' of cement on top of plug, thereby plugging off pl	Drawer D. Mc	nument, New Mex	cico 88265			illilli	
Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Prisselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf, 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequested 26% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. The Propose save described Proposed Programs if Proposed is to describe and better. Thereby certify that the information above is true and complete to the best of my knowledge and better. Title Carmer Lea 21. Lea 22. Appens. Dote Work will start 22. Appens	4. Location of Well unit LETT	ER LOC	ATED 660 FE	ET FROM THE NOTE	LINE	VIIIIII	
Lea 11. Exposure Oper Propose Department of the State of States o		Y 7 4-	25				
PROPOSED CASING AND CEMENT PROGRAM Size of Hole Size of Hole Size of Casing weight per foot Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off plug, set bridge plug at 5880' with 50' of cement on top of plug, thereby plugging off Pusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7' csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. Thereby certify that the information above is true and complete to the best of my knowledge and belief. Table Table	AND 990 FEET FROM	THE West LIN	E OF SEC.	Triffirm	TITITI	12. County	11111111
21. Clavelions (Show whether DF, RT, etc.) 21A. Kims & Status Plug. Bond 21E. Drilling Contractor 22. Approx. Date Work will start 2-14-77 23. PROPOSED CASING AND CEMENT PROGRAM No change SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 ggl. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. HILABOVE SPACE DESCRIBE PROPOSED PROSRAMS IF PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED PROSRAMS IF PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED PROSRAMS IF PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED PROSRAMS IF PROPOSED IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN						Lea	
21. Clavelions (Show whether DF, RT, etc.) 21A. Kims & Status Plug. Bond 21E. Drilling Contractor 22. Approx. Date Work will start 2-14-77 23. PROPOSED CASING AND CEMENT PROGRAM No change SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 ggl. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. HILABOVE SPACE DESCRIBE PROPOSED PROSRAMS IF PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED PROSRAMS IF PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED PROSRAMS IF PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED PROSRAMS IF PROPOSED IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN	4444444	<i>HHHH</i>	/////////////////////////////////////	/////////////////////////////////////	4444	Mille	
21. Clavelions (Show whether DF, RT, etc.) 21A. Kims & Status Plug. Bond 21E. Drilling Contractor 22. Approx. Date Work will start 2-14-77 23. PROPOSED CASING AND CEMENT PROGRAM No change SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 ggl. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. HILABOVE SPACE DESCRIBE PROPOSED PROSRAMS IF PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED PROSRAMS IF PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED PROSRAMS IF PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED PROSRAMS IF PROPOSED IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN PROPOSED HEN PRO- THE TOWL GIVE BLOWGUT PREVENTED PROPOSED HEN							
21. Llevations (Show whether DF, RT, etc.) 21A. Kind & Stutus Plug. Bond 21B. Drilling Contractor 22. Approx. Date Work will start 2-14-77 23. PROPOSED CASING AND CEMENT PROGRAM No change SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. WHAROVE SPACE DESCRIBE PROPOSED PROGRAM: If PROPOSAL IS TO DEEPEN ON PLUS BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED BLW PAGE THE ZOUR. GIVE BLOWD PREVENTER MOGRAM, IF AND. Thereby certify that the information above is true and complete to the best of my knowledge and belief. Signed Agree Agree Describe Proposed Deposition to the best of my knowledge and belief. Title Cagness. Date 2/917		HHHHHH	/////////////////////////////////////	9. Proposed Depth	9A. Formatio	on .	20, Rotary or C.T.
21. Elevations (Show whether DF, RT, etc.) 21A. Kims 6 Starus Plug. Bond 21B. Drilling Contractor 2-14-77 22. PROPOSED CASING AND CEMENT PROGRAM No change SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. Signed Age: Whe scorout Provided Model of the Description of the Description of the Date of the Date 2/177 Tale Cagassa. Date 2/177 Signed Age: Whe scorout Provided Model of the Description of the Date 2/177 Tale Cagassa. Date 2/177				4180 S	an Andre	es	
Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone cgs. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. HABOVE SPACE DESCRIBE PROPOSED PROSRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED BLW PARTITION OF THE PROPOSED BLW PARTITI	21. Elevations (Show whether DI	F, RT, etc.) 21A. Kino	& Status Plug. Bond 2	1B. Drilling Contractor		1	
PROPOSED CASING AND CEMENT PROGRAM No change SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN ON PLUG BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED BLW 26 The ZONE GIVE BLOWNLY PREVENTER PROPOSED BLW 26 THE ZONE OF THE COURT PREVENTER PROPOSED BLW 26 THE ZONE OF THE COURT PREVENTER PROPOSED BLW 26 THE ZONE OF THE COURT PREVENTER PROPOSED BLW 26 THE ZONE OF THE ZONE OF THE COURT PREVENTER PROPOSED BLW 26 THE ZONE OF THE ZONE O						2-14-	77
Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt vater in San Andres zone. Refer NMOCC Order SWD-181. The zone give blowout Presenter Proposed, if ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. Signed Ways Ways Title Lagrages Date 24 177	23,		DRODOSED CASING AND	CEMENT PROGRAM	No cha	nge	
Propose to pull two strings of tbg., set bridge plug at 6850' with 50' of cement on top of plug, set bridge plug at 5800' with 50' of cement on top of plug, thereby plugging off Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. The Above space Describe Proposed Program: If Proposal is to Deepen on Plug Back. Give Data on Present Productive zone and proposed blue 24. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any. Title Type 2016 for the blowdur preventer reagers. If any.	•						FST YOP
Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN ON PLUG BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED BEN 25% TIPE ZONE GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. The ZONE GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. Signed Agree Date Title Title Date Date Date Date Date Date Date Dat	SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	ISACKS O	F CEMENT	231. 101
Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN ON PLUG BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED BEN 25% TIPE ZONE GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. The ZONE GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. Signed Agree Date Title Title Date Date Date Date Date Date Date Dat			<u> </u>				
Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN ON PLUG BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED BEN 25% TIPE ZONE GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. The ZONE GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. Signed Agree Date Title Title Date Date Date Date Date Date Date Dat					+		
Fusselman zone perfs. fr. 6884' to 6919' and Drinkard zone csg. perfs. fr. 5856' to 5928'. Perf. 7" csg. opposite San Andres zone fr. approx. 4068' to 4180', acidize with 4500 gal. double inhibited and sequestered 28% HCl acid and start disposing of produced salt water in San Andres zone. Refer NMOCC Order SWD-181. IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN ON PLUG BACK. GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED BEN 25% TIPE ZONE GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. The ZONE GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. Thereby certify that the information above is true and complete to the best of my knowledge and belief. Signed Agree Date Title Title Date Date Date Date Date Date Date Dat			*		ļ	ŀ	
I hereby certify that the information above is true and complete to the best of my knowledge and helief. Signed are Title engineer Date 2/9/77	plug, set bridge p Fusselman zone per Perf. 7" csg. oppo	olug at 5800' wi ffs. fr. 6884' t osite San Andres and sequestered	to 50° of cements of 6919' and Dries zone fr. appro	inkard zone csg.	perfs.	fr. 5856 dize with	' to 5928'. 4500 gal.
	TIVE ZONE. GIVE BEOMOUT PREVE	A L L L L L L S G L L L L L L L L L L L L			ON PRESENT	PRODUCTIVE ZONE	AND PROPOSED HEW 250
(This space so Agus lighted by	A						e as k and Ti
	(This space)	Orthic Haust pa				FE	B T4 13//

APPROVED BY _____ Dist 1, Supy, TITLE__

CONDITIONS OF APPROVAL, IF ANY:

ETTIMED

FEE 1 1977

CL C. SERALLON COMM.