

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name Ida Wimberley
3. Address of Operator Drawer "D", Monument, New Mexico 88265		9. Well No. 8
4. Location of Well UNIT LETTER G 1650 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 25 TOWNSHIP 25-S RANGE 37-E NMPM.		10. Field and Pool, or Wildcat Justis Tubb Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) 3073' DF		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	P&A Drinkard zone only <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pulled production equipment from Tubb-Drinkard and Fusselman zones.
Set ret. B.P. at 6000' with 2 sx. sand on top. Squeezed Tubb-Drinkard zone 7" casing perfs. 5874' to 5924' with 100 sx. Class "C" and 200 sx. Expanding cement. Drilledout cement and tested with 800# O.K. Drinkard zone P&A. Continued with remedial work on Fusselman zone.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNED <u><i>M. O. Black</i></u>	TITLE <u>Supvr., Adm. Services</u>	DATE <u>6-28-72</u>	
APPROVED BY <u>Joe D. Ramey</u>	TITLE <u>Dist. I, Supv.</u>	DATE <u>JUN 30 1972</u>	

RECEIVED

JUN 26 1972

OIL CONSERVATION COMM.
HOBLE, L. D.