

COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes GH
C-102 and C-101
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR APPLICATIONS TO OIL OR TO PERFORM OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO OIL (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ Dual GAS WELL ☐ OTHER ☐

Name of Operator
Atlantic Richfield Company

Address of Operator
P. O. Box 1710, Hobbs, New Mexico 88240

Location of Well
UNIT LETTER A 430 FEET FROM THE North LINE AND 760 FEET FROM
THE East LINE, SECTION 25 TOWNSHIP 25S RANGE 37E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3073' GR

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-11478

7. Unit Agreement Name

8. Form of Lease Name
State "Y"

9. Well No.
7

10. Field and Pool, or Wildcat
Justis Blinebry/Montoya

12. County
Lea

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER <u>Add Perfs in Montoya & Acidize</u> ☒	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 7000', PBD 6994'. Present perfs Bly 5366-73', 5382-88', 5399-5405', 5414-32, 5038, 5319'. Montoya perfs 6930-60'. Propose to add Montoya perfs & treat Montoya and Blinebry with acid in the following manner:

1. Rig up, kill well, install BOP & POH w/dual completion assemblies.
2. Retrieve Model D pkr @ 6877' or push to PBD.
3. Perf add'l Montoya zone 6868-78'.
4. RIH w/pkr & RBP, set BP @ bottom & pkr @ approx 6895'. Acidize Montoya perfs 6930-60' w/2000 gals 15% HCL w/additives.
5. Reset BP @ approx 6910', pkr @ 6820', acidize Montoya perfs 6868-78' w/500 gals 15% HCL w/additives.
6. Release pkr, retrieve BP, reset @ approx 5500' & pkr @ 4990'. Acidize Bly perfs 5038-5432' w/3000 gals 60/40 15% HCL/xylene acid. POH w/pkr & RBP.
7. Run dual compl assemblies and return to production.

10. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Dist. Drlg. Supt. DATE 2/14/78

APPROVED BY [Signature] TITLE [Blank] DATE [Blank]

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 14 1978

OIL CONSERVATION COMM.
HOBBS, N. M.