

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYField Office Las CrucesLease No. 032579(e)Unit Lease

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING.....	<input type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT.....	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY.....	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL.....	<input type="checkbox"/>		<input type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 13, 1952Well No. 325-2 is located 920 ft. from N line and 650 ft. from E line of sec. 25SE 1/4 (1/4 Sec. and Sec. No.) 253 (Twp.) 37E (Range) N 37° 15' W (Meridian)Justis (Field) Lea (County or Subdivision) New Mexico (State or Territory)The elevation of the derrick floor above sea level is 3054 ft. approx.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill a well using rotary tools to approx. 7100' to test and produce the Fusselman Formation. The casing program is to set approx. 600' of 13 3/8" casing cemented to surface, to set approx. 3350' of 9 5/8" casing cemented to the base of 13 3/8" casing using a BV collar at the top of the salt section and cementing from the bottom of 9 5/8" to that point, to set 7" casing to T.D. using BV collar at top of Fusselman formation and cementing to base of 9 5/8" casing. Formation logs will be taken and copies of all tests will be furnished. State and Federal regulations will be complied with.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Hamilton Bone Oil Company, Ltd.Address P.O. Box 1341Jal., New MexicoPhone 5591By G. E. BurtonTitle Division Superintendent