

NEW MEXICO OIL CONSERVATION COMMISSION
SOUTHEAST NEW MEXICO PACKER LEAKAGE TEST

Operator Westates Petroleum Company		Lease Carlson B 26			Well No. 6	
Location of Well	Unit P	Sec 26	Twp 25	Rge 37	County Lea	
	Name of Reservoir or Pool		Type of Prod (Oil or Gas)	Method of Prod Flow, Art Lift	Prod. Medium (Tbg or Csg)	Choke Size
Upper Compl	Blinsbry		Oil	P	Tubing	None
Lower Compl	Tubb Drinkard		Oil	P	Tubing	None

FLOW TEST NO. 1

Both zones shut-in at (hour, date): **0645 - April 13, 1967**

Well opened at (hour, date): 0645 - April 14, 1967	Upper Completion	Lower Completion
Indicate by (X) the zone producing.....	X	
Pressure at beginning of test.....	565	230
Stabilized? (Yes or No).....	*No	*No
Maximum pressure during test.....	565	264
Minimum pressure during test.....	37	230
Pressure at conclusion of test.....	37	264
Pressure change during test (Maximum minus Minimum).....	- 528	+ 34
Was pressure change an increase or a decrease?.....	Decrease	Increase
Well closed at (hour, date): 0645 - April 15, 1967	Total Time On Production 24 Hours	
Oil Production During Test: 89 bbls; Grav. 37.2	Gas Production During Test 58.0 MCF; GOR 651 Cu. Ft./Bbl.	
Remarks * Both zones continued to build up during 24 hour shut-in period.		

FLOW TEST NO. 2

Well opened at (hour, date): 0645 - April 16, 1967	Upper Completion	Lower Completion
Indicate by (X) the zone producing.....		X
Pressure at beginning of test.....	663	272
Stabilized? (Yes or No).....	*No	Yes
Maximum pressure during test.....	742	272
Minimum pressure during test.....	663	29
Pressure at conclusion of test.....	742	29
Pressure change during test (Maximum minus Minimum).....	+ 79	- 243
Was pressure change an increase or a decrease?.....	Increase	Decrease
Well closed at (hour, date): 0645 - April 17, 1967	Total time on Production 24 Hours	
Oil Production During Test: 40 bbls; Grav. 36.7	Gas Production During Test 44.9 MCF; GOR 1123 Cu. Ft./Bbl.	
Remarks * Blinsbry zone continued to build up during shut-in period.		

I hereby certify that the information herein contained is true and complete to the best of my knowledge.

Approved _____ 19 _____ New Mexico Oil Conservation Commission	Operator Westates Petroleum Company By W. F. Stull <i>W. F. Stull</i>
By _____ Title _____	Title Production Superintendent Date 4-20-67

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.

3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized and for a minimum of two hours thereafter, provided however, that they need not remain shut-in more than 24 hours.

4. For Flow Test No. 1, one zone of the dual completion shall be shut-in at the normal rate of production while the other zone remains shut-in. Such test shall be continued until the flowing wellhead pressure has become stabilized and for a minimum of two hours thereafter, provided however, that the flow test need not continue for more than 24 hours.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the previously shut-in zone is produced.

7. All pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked with a deadweight tester at least twice, once at the beginning and once at the end, of each flow test.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the appropriate District Office of the New Mexico Oil Conservation Commission on Southeast New Mexico Packer Leakage Test Form Revised 11-1-58, together with the original pressure recording gauge charts with all the deadweight pressures which were taken indicated thereon. In lieu of filing the aforesaid charts, the operator may construct a pressure versus time curve for each zone of each test, indicating thereon all pressure changes which may be reflected by the gauge charts as well as all deadweight pressure readings which were taken. If the pressure curve is submitted, the original chart must be permanently filed in the operator's office. Form C-116 shall also accompany the Packer Leakage Test Form when the test period coincides with a gas-oil ratio test period.

[illegible]