

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instruction on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 034117(b)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER Shut in	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR Atlantic Richfield Company	7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR P. O. Box 1978, Roswell, New Mexico 88201	8. FARM OR LEASE NAME Crosby "B"
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330' FSL & 2310' FWL	9. WELL NO. 1
14. PERMIT NO.	10. FIELD AND POOL OR WILDCAT Jalmit Yates
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3016' GR	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28, T25S, R37E
	12. COUNTY OR PARISH Lea
	13. STATE N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

☐
☐
☐
☒
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well has been shut in since 1962. It is non-commercial and no remedial possibilities exist. We propose to plug and abandon as follows:

1. Set 7" 24# CIBP @ 2375' and cap w/2 sx of cement.
2. Perforate 7" casing w/4 holes @ 1275' and pump in 100 sx of cement, leaving 100' of cement inside casing.
3. Place 10 sx of cement in top of well.

Erect dry hole marker. Clear and level location.

AMENDMENT: Increase cement plug on top of above trial plug from 2 sacks to a 50 foot (minimum) cement plug.
Hole to be filled with mud between plugs.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ed Ditcher

TITLE

Dist. Drlg. Supervisor

DATE

4/16/71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED
AS AMENDED
APR 19 1971ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED

APR 27 1971

OIL CONSERVATION COMM.
HOBBS, N. M.