

NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

OFFICE 000

DUPLICATE

SUBMIT THIS NOTICE IN TRIPPLICATE TO THE DISTRICT OFFICE, OIL CONSERVATION COMMISSION, BEFORE THE WORK SPECIFIED IS TO BEGIN. A COPY WILL BE RETURNED TO THE OWNER ON WHICH WILL BE GIVEN THE APPROVAL, WITH ANY MODIFICATIONS CONSIDERED ADVISABLE, OR THE REJECTION BY THE COMMISSION OR AGENT, OF THE PLAN SUBMITTED. THE PLAN AS APPROVED SHOULD BE FOLLOWED, AND WORK SHOULD NOT BEGIN UNTIL APPROVAL IS OBTAINED. SEE ADDITIONAL INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.

INDICATE NATURE OF NOTICE BY CHECKING BELOW

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (S/RO)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(PLACE)November 5, 1956
(DATE)

GENTLEMEN:

FOLLOWING IS A NOTICE OF INTENTION TO DO CERTAIN WORK AS DESCRIBED BELOW AT THE

Humble Oil & Refining Company C. T. Bates WELL NO. 1 IN C
(COMPANY OR OPERATOR) (UNIT)

NE 1/4 NW 1/4 OF SEC. 29, T. 25-S, R. 17-E, (MAPA, Crosby-Devonian) POOL
(60-ACRE SUBDIVISION)

Lea COUNTY.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Plug and abandon well as follows:

1. Set cement plug in 8-5/8" casing from 3111 to 3111 feet and bradenhead squeeze. Set cast iron bridge plug at approximately 3111.
2. Place 10-foot cement plug in top of 8-5/8-inch casing.
3. Remove wellhead and place marker as required by NMOCC.

Note: Drilled well to total depth of 9134 feet. Set cement plug from 9134 to 8934 with 65 sacks. Set cement plug from 3715 to 3515 with 65 sacks. (8-5/8-inch casing set at 3618). Drilled cement to 3565. Tested with 1000 psi.

Current producing interval is through perforations in 8-5/8-inch casing from 3292 to 3306. Casing was also perforated from 3411 to 3426. This interval plugged off by setting cement retainer at 3386, squeezing with 50 sacks of cement, and then setting cast iron bridge plug at 3311.

APPROVED _____, 19____
EXCEPT AS FOLLOWS:

Humble Oil & Refining Company
COMPANY OR OPERATOR

APPROVED _____
OIL CONSERVATION COMMISSION

BY E. J. Fischer

FOR THE Agent
SEND COMMUNICATIONS REGARDING WELL TO:

Humble Oil & Refining Company

TITLE _____
ADDRESS Box 2347, Hobbs, N.M.