## EXICO OIL CONSERVATION COMM. SION

SANTA FE, NEW MEXICO

## **MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any medications bensidered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of

| Indicate nature of r  | otice by checking below:  Rules and Regulations  OIL CONSTRUCTION COMMISS  HOBES-OFFICE               |
|---|---|
| NOTICE OF INTENTION TO TEST CASING SHUT-OFF   | NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL   |
| NOTICE OF INTENTION TO CHANGE PLANS   | NOTICE OF INTENTION TO PULL OR<br>OTHERWISE ALTER CASING  |
| NOTICE OF INTENTION TO REPAIR WELL  | NOTICE OF INTENTION TO PLUG WELL  |
| NOTICE OF INTENTION TO DEEPEN WELL  |   |
| J   | al, New Mexico December 17, 1951 Place Date   |
| OIL CONSERVATION COMMISSION,<br>Santa Fe, New Mexico  |   |
| Gentlemen:  | •   |
| Following is a notice of intention to do certain work as d  | escribed below at the   |
| Olsen Blount Oil Co. Coll Company or Operator Leage   | Well No A-1 in SW NE  |
| of Sec. 29, T25S, R37h  | , N. M. P. M., langlic tattix Field   |
| Lea County.   | 1610  |
|   | S AND REGULATIONS OF THE COMMISSION   |
| <pre>nan 278' of 10 3/4" 32# surface casis sacks - circulated to surface - Plug Cemented plug to be drilled after 4 F for 30 minutes to test casing shut of</pre> | ng set at 287'. TD 288'. Used 200 down 4 PM 12-16-51.   |
| Cemented plug to be drilled after 4 F for 30 minutes to test casing shut of   | ng set at 287'. TD 288'. Used 200 down 4 PM 12-16-51.  PM 12-17-51. 1000# will be applied and h left. |
| Cemented plug to be drilled after 4 F for 30 minutes to test casing shut of   | ng set at 287'. TD 288'. Used 200 down 4 PM 12-16-51.   |
| Cemented plug to be drilled after 4 F for 30 minutes to test casing shut of   | Olsen Blount Oil Co.  Company or Operator  By Company or Operator  Position Geological Engineer       |