

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

P. O. BOX 1900
HOBBS, NEW MEXICO 88240

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR ARCO Oil and Gas Company
Division of Atlantic Richfield Company

3. ADDRESS OF OPERATOR
P. O. Box 1710, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 1980' FEL - Unit "O"

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

Detailed Report of Wellhead Repair &
Pipe Annulus to Surface

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 3/22/85 dug out cellar to 14' below ground level. Located 13-3/8" OD csg. Original WH is screwed into 10-3/4". Cmt was circ out 10-3/4" x 8-5/8", and 8-5/8" x 7" annuli 3/16/85. Cut off 7" csg. Inst 10V x 8rd 7" csg cplg, 1 riser, 7" 23# x 8' w/2 bell nipples & 1 Larkin 2000# WOG tbg head w/2 - 2" outlets 2' above ground level. Riser pipes are in place on 10-3/4" x 8-5/8" csg & 8-5/8" x 7" csg above ground level w/valves @ surface. Tested wellhead & 7" riser w/1000# for 30 mins OK. Eddy Seay w/NMOCD checked new WH assembly & cellar 3/22/85. Pmpd 165 sx C1 H Neat down 13-3/8" x open hole annulus & loaded open hole w/cmt, filled cellar to 3" short of top of 13-3/8" colg in base of cellar. Additional squeeze work, Jalmat perms, stimulation and testing reported separately on Form 9-331.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Elizabeth A. Rusk*

TITLE Drlg. Engr.

DATE 5/9/85

(This space for Federal or State office use)

APPROVED BY

ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

MAY 13 1985

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO

General Purpose Worksheet

Subject	R.S. Crosby A. No. 1		Page No.	01
File	New WH in place	By	Bush	Date 5-9-85

