

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

NOV 4 1947

HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

3 March, 1947

Date

Midland, Texas

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Kerr-McGee

Oil Industries, Inc.WinninghamWell No. 1

in the

Company or Operator

Lease

Str. SE/NWof Sec. 30T. 26SR. 37E

N. M. P. M.,

Cooper-Jal

Field,

Lea

County.

The dates of this work were as follows:

27 February 1947 - 28 February 1947

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on 27 February 19 47

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3 plugs set as follows: Work done by Halliburton

10 3/4" left in hole to 363.

1175 to 1220, Top Salt Section, cemented with 18 sx.

2605 to 2650, Base Salt Section, cemented with 18 sx.

2991 to 3034, Sulphur Water Zone, cemented with 17 sx.

Mudded between plugs, using drilling mud of 42 viscosity and 10.6 weight plug
25-30 sacks impermex. Pressure retained was hydrostatic, plus 400 lb. circulation pressure.

Witnessed by

Name

Company

Title

Subscribed and sworn before me this 28th

I hereby swear or affirm that the information given above is true and correct.

day of February, 19 47

Name

Position

Geologist

Representing

Kerr-McGee Oil Industries, Inc.
Company or OperatorMy commission expires 1 June 1947

Address

Box 243Midland, Texas

Remarks:

APPROVED

Date NOV 4 1947

Roy Yarbrough
Name
G.S. INSPECTOR
Title