

RECEIVED

DEC 18 1950

OIL CONSERVATION COMMISSION  
HOEBS-OFFICE

## OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

December 11, 1950

Date

Jal, New Mexico

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
**R. OLSEN OIL COMPANY** **Winningham** Well No. **4** in the

Company or Operator **C 42 SW SE** of Sec. **30**, T. **25S**, R. **37E**, N. M. P. M.,  
**Cooper-Jal** Field **Lea** County.

The dates of this work were as follows: **December 1, 1950 & December 10, 1950**

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on \_\_\_\_\_ 19\_\_\_\_  
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Run 3125' ~~5 1/2"~~ **5 1/2"**, ~~2 1/2"~~ **17#**, J55 oil string set at 3145'. Used 400 sacks cement 200 at shoe-200 thru 2 stage tool set at 1195'. Cement circulated to surface. Plug down at 1 AM Dec. 1, 1950. #OC TD 3150.

Tested Dec. 10, 1950. Drilled float, applied 1000# and held for 30 min. with 10# pressure drop. Drilled shoe-applied 1000# and held for 30 min. 0# press. drop.

Witnessed by **French** Name **R. OLSEN OIL COMPANY** Company Title

Subscribed and sworn before me this \_\_\_\_\_

**11th** day of **December**, 19 **50**

*Clyde L. ...*  
Notary Public

My Commission Expires Sept. 2, 1953

My commission expires \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

Name **Henry Watson**

Position **Geol. Engr.**

Representing **R. OLSEN OIL COMPANY**  
Company or Operator

Address **Drawer "Z", Jal, New Mexico**

Remarks:

DEC 18 1950  
Date

*Ray ...*  
Name  
Title