

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Meridian Oil Inc

3. Address of Operator

P.O. Box 51810, Midland, TX 79710-1810

4. Well Location

Unit Letter I : 1989 Feet From The South Line and 660 Feet From The East Line

Section 31

Township 25-S

Range 37-E

NMPM Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

2996' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Move from Jalmat oil to Jalmat gas ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/24/91 TIH w/ 7" csg scrapper to 2676'. TOH, TIH w/ 4-1/2" csg scrapper to 3000'.

5/25/91 Ran GR/CCL log 3050'-2750'. Set 4-1/2" CIBP @ 2990'. Test csg to 1000#. Perf Yates w/ 3-3/8" select fire gun 2785'-2936', 24 shots. TIH w/ 4-1/2" pkr, set @ 2954'. Test CIBP to 3800#. Spot 150 gals 15% NEFe @ 2936'. Pull pkr to 2706'. Reverse acid & set pkr. Acidize w/ 1500 gal 15% NEFe HCl & 35 BS.

5/26/91-

5/27/91 Frac w/ 31,000 gals 50 Quality CO2 foam & 42,000# 12/20 Brady Sand. Open on 1/4" choke.

5/28/91 TIH w/ 2-3/8" notched collar, 1 jt 2-3/8" tbg, 2-3/8" S.N. & 2-3/8" tbg. Wash sand 2770'-2990'. Pull tbg to 2763'. TIH w/ 2" x 1-1/4" x 16' RHBC pmp & 107 3/4" rods.

5/29/91 Turn to production. Load & test tbg.

6/12/91 Lower tbg 68', tag sand @ 2830'. Wash sand 2830'-2990'. Circ clean. PU to 2800'. RIH, tag 2950'. Circ clean. PU to 2800'. RIH, tag @ 2970'. Circ Clean.

6/13/91 TIH w/ notched collar, tag 2930'. Clean out to 2990'. Circ clean w/ foam air. PU & hang tbg @ 2822'. Run pmp & rods. Turn to production 6/13/91.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Roxann Scholz

TITLE Production Asst

DATE 5/18/92

TYPE OR PRINT NAME Roxann Scholz

TELEPHONE NO. (915)688-6943

(This space for State Use) FOR APPROVAL BY JERRY SEXTON
DISTRICT SUPERVISOR

APPROVED BY

TITLE

DATE

MAY 27 '92

CONDITIONS OF APPROVAL, IF ANY: