

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

**Clean Blount Oil Co.** Drawer #21 Jal, New Mexico  
Company or Operator Address  
Legal Lease Well No. 2 in NE SE of Sec. 31 T. 25S  
R. 37, N. M. P. M. Langlie-Hattix Field, Lea County.  
Well is 1900 feet South of the South line and 660 feet west of the East line of Sec. 31-25S-37E  
If State land the oil and gas lease is No. Assignment No.  
If patented land the owner is M. F. Legal Address  
If Government land the permittee is Address  
The Lessee is Clean Blount Oil Co. Address Drawer #21 Jal, New Mexico  
Drilling commenced 8-10-51 19 Drilling was completed 9-29-51 19  
Name of drilling contractor Clean Blount Drilling Co. Address  
Elevation above sea level at top of casing 2989 feet.  
The information given is to be kept confidential until 19

## OIL SANDS OR ZONES

No. 1, from 2780 to 2952 No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
10 3/4	32	8	Natl	293	NO SHO				Surface
7	20	8	Natl	2771	NO SHO				Oil string

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
13 3/4	10 3/4	305	200	NO SHO		
8 5/8	7	2778	400 - 200 at shoe - 200 thru 2-stage tool set at 1103'			

## PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set  
Adapters — Material Size

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Nat Acid	500 Gals	9-1-51	2778 - 2827	
2 1/2	2	Nat Acid	300 Gals	9-28-51	2800 - 2950	2950

Results of shooting or chemical treatment Chemical treatment - No results Nitro 7 MCPPD - 5 bbls oil.

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from 0 feet to 2952 feet, and from feet to feet  
Cable tools were used from feet to feet, and from feet to feet

## PRODUCTION

Put to producing 9-30 51  
The production of the first 24 hours was 5 barrels of fluid of which 100% was oil; %  
emulsion; % water; and % sediment. Gravity, Be  
If gas well, cu. ft. per 24 hours 7,000,000 Gallons gasoline per 1,000 cu. ft. of gas  
Rock pressure, lbs. per sq. in.

## EMPLOYEES

Hamm Driller Kellewell Driller  
Windsor Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 8th

day of October 19 51

Notary Public

My Commission expires My Comm. exp: June 1, 1955

Jal, New Mexico October 4, 1951

Name Dewey Watson

Position Geological Engineer

Representing Clean Blount Oil Co.

Address Drawer #21 Jal, New Mexico

# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
2500	2640	140	White and red sand, anhydrite
2640	2660	20	Anhydrite, shale, sand
2660	2700	40	Anhydrite, brown limestone
2700	2760	60	Brown limestone
2760	2770	10	Brown limestone, anhydrite
2770	2780	10	Missing
2780	2785	5	Dolomite, anhydrite, sand
2785	2805	20	Dolomite, and sand FQG
2805	2810	5	Sand, dolomite
2810	2827	17	Dolomite, sand
2827	2830	3	Sand, dolomite
2830	2835	5	Dolomite
2835	2845	10	Sand, dolomite, shale
2845	2865	20	Loose, sand, dolomite, shale
2865	2875	10	Dolomite, pyrite
2875	2885	10	Dolomite, pyrite, sand, shale
2885	2890	5	Sand, dolomite, shale
2890	2952	62	Pyrite, dolomite, sand, shale
	TD		
			<u>Geological Tops</u>
			Top Anhydrite 945
			Top Yates 2778