

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Las Cruces
032510 (a)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill, deepen or plug-back. Another form is provided for such proposals.)

OIL
WELL ☐

GAS
WELL ☒

OTHER

DRY ☐

1. OPERATOR

Pan American Petroleum Corporation

2. ADDRESS

Box 68 Hobbs, New Mexico

3. LOCATION (Report location clearly and in accordance with any State requirements. If see also space 17 below)

990' FSL x 1659 FWL.

*Inspected location & found
everything okay for P & A.
9-20-62 E J Hubble*

4. IF EXIST, ADDRESS OF WELL OWNER

5. OWNER'S SIGNATURE

6. NAME OF TRUSS NAME

L. W. Gregory "A"

7. WELL NO.

22

8. FIELD AND POOL, OR WILDCAT

Jalnet (Gas)

9. SEC., T., R., M., OR B.L.S. SURVEY, IN B.L. & M.

Sec. 31, T-25-S, R-37-E, NMPH

10. ROUGHNESS Surface Floor

2967

Rotary Kelly Bucking

NA

Rotary Table

NA

Ground

NA

Other

NA

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

15. INDICATE BELOW BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA

NOTICE OF INTENTION TO: (Submit in triplicate)

WATER SHUT-OFF ☐

FULL OR ALTER CASING ☐

FRACURE TREAT ☐

MULTIPLE COMPLETE ☐

SHOOT OR ACIDIZING ☐

ABANDON ☐

REPAIR WELL ☐

CHANGE PLANE ☐

SUBSEQUENT REPORT OF: (Submit in duplicate, except abandonment.)

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACURE TREATMENT ☐

ALTERING CASING ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT (triplicate) ☒

(Note: Report results of multiple completion on Well Completion or Recompletion and Log form)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.

In accordance with Form 9-331, a Approved April 16, 1962 this well was plugged and abandoned as follows:

Casing Cut and/or Pulled from

8 5/8" - 1404'
10 3/4" - 1069'
13 " - 450'

Cement Plugs

25 Sx @ 2850'
30 Sx @ 1428'
50 Sx @ 1105'
95 Sx @ 450'
30' - 100' @ Surface

All intervals filled with heavy mud laden fluid. Erected P & A Marker. Restored ground to its natural contour.

NOTED

MAY 31 1962

HUBBLE

MAY 29 1962

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing as to any work or operation performed is a true and correct report of such work or operation.

SIGNED

TITLE

Area Superintendent

DATE

5/25/62

(This space for Signature)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

SEP 21 1962

E. W. STANDLEY
DISTRICT ENGINEER

* See Instructions On Reverse Side