


FORM C-105



NEW MEXICO OIL CONSERVATION Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, er its proper agent not more than twenty days after completion of well. Follow instructions in the

	AREA 640 A	ACRES		it with (?)	. SUBMIT IN T	ne Commission. In RIPLICATE, FORI PROPERLY FILLI	M C-110 WIL			
	ATE WELL (	CORRECTLY						_		
	_	Company or	Kell	<b>y</b> E	30x 5671,	Roswell	Ne Yad	gxic	m 05~8	
Sbe	Lease	)	Well No				ec	***************************************	, T25#S	
37-1	;, N	N. M. P. M., et south of	the North	line and	een feet	west of the Ea	st line of		County	
f State la	nd the oil a	nd gas lease	is No		Assign	ment No				
f Govern	ment land t	he permitte	e is	·····		,	Address			
									l, New Mexico	
									19.50	
					feet.		Address	Θ	dessa, Texas	
								19		
iic iiioii	22000		• • • • • • • • • • • • • • • • • • • •		SANDS OR 2					
io. 1. fro	M23.7-()		to					to.		
No. 2, fro	m		to		No. 5	, from	•••••	to.		
lo. 3, fro	m		to		No. 6	5, from	***************************************	to.		
				IMPOR'	TANT WATE	R SANDS				
					hich water ros				-	
,					ASING RECO					
				1	1		1 prom	ORATED		
SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	FROM	TO	PURPOSE	
0 3/4	30	8	Seam	269	Texas					
7	20	8	Seam	2946	Hallib	urton	-			
						<del></del>	·			
	10 3/4	269 1350	100 300 200	Hal	lliburtor				M	
8 5,	/8 /1	2945	200							
					GS AND ADA					
dapters	— Material							••••••	······································	
			RECORD	OF SHOO!	TING OR CH	EMICAL TREA			· · · · · · · · · · · · · · · · · · ·	
SIZE	SHELL	USED	EXPLOSIV CHEMICAL	EXPLOSIVE OR CHEMICAL USED		TY DATE DEPTH SHOT DEPTH		DEPTH CLEANED OUT		
	5#	ים י	upont		400	10/28/	50 311	0-32	70 3275	
	<u> </u>									
	f chooting (	or chemical	treatment	: Inc	crease fi	rom 20 to	60 EOI	21)		
vesurus o										
						D SPECIAL T			atta da Nameta	
f drill-ste	em or other	special test	s or deviati	on surveys v			separate sn	ieet and	attach hereto.	
	_	3.00000	0	e	TOOLS USE			foot	tofe	
									tofe	
able too.	is were use	u 110111			PRODUCTIO					
ut to pro	oducing	10/30								
_		•				s of fluid of wh	ich <b>100</b> .	%	was oil;	
mulsion;		% water	; and	% se	ediment. Grav	vity, Be		•••••		
f gas wel	l, cu. ft. per	r 24 hours	250,	.000es	tGallor	ns gasoline per	1,000 cu. ft	. of gas.		
lock pres	ssure, lbs. p	er sq. in	ξ	350	***************************************					
					EMPLOYEES				- ···	
									Drill , Drill	
***************************************		•				OTHER SID			, Dilli	
hereby s	wear or affi	irm that th						of the we	ell and all work done o	
-	s can be de						_			
Subscribe	d and sworr	n to before	me this	10th		Roswell	New_	Mexi.c	11/8/5	
	~			, 19			Place	1111	1400° to	
ay OI	<u></u>				Ho	sition	Owner	ruf	7007	
<u> </u>		<b>ユ</b> ウン	No.	otary Public		presenting	John M	. Kel	iy /	
						1	Con	npany or	Operator	

My Commission Captinos June 128, 1253

My Commission expires.....

Address Box 5671, Roswell, N.M.

FORMATION RECORD											
FROM	то	THICKNESS IN FEET	FORMATION								
Done o		2000 S 2000 S									
Base Sal	240 <b>0</b>										
2400	2565	165	Br Lime								
2565	2850	285	Yates Sand								
2850	3110	160	Lime								
3110	3343	233	Sand and Lime								
	,	-	Top Yates 2565								
			Top S. R. 2995								
				:							
				:							
				:							
		7									
			•								
				-							
افدر	1 20 19 17 T			*.							
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	į										
-											