Form 9-331

SUBMIT IN TRIPLICA'. HNIT! STATES

			appros t Bure		o. 42 -R	142
			THE RESERVE			
5.	LEASE	DESIG	NATION	AND	SERIAL	NO.

(May 1963)	DEPARTMENT THE INTERIOR (Other Instructions of Other Instructions				
(Do not use this fo	DRY NOTICES AND REPORTS ON WELLS orm for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTER	OR TRIBE NAME		
OIL GAS WELL WELL	OTHER	7. UNIT AGREEMENT NA	ME		
2. NAME OF OPERATOR		8. FARM OR LEASE NAM	E		
El Paso Natur	al Gas Company	Gregory Fed	Gregory Federal		
3. ADDRESS OF OPERATOR	M	9. WELL NO.			
4. LOCATION OF WELL (Re See also space 17 below At surface		2-Y 10. FIELD AND POOL, OR WILDCAT Crosby Devonian 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
76U. F	NL, 1650' FWL	Sec 33, T-25-	Sec 33, T-25-S, R-37-E		
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH			
	3,002' Gr.	Lea	New Mexico		
16.	Check Appropriate Box To Indicate Nature of Notice, Report,	or Other Data			

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:				
	11				٢			
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL,			
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING			
SHOOT OR ACIDIZE		ABANDON*		SHOOTING OR ACIDIZING	ABANDON MENT*			
REPAIR WELL		CHANGE PLANS		(Other) Unsuccessful co		χ		
(Other)				(Note: Report results of mul	tiple completion on Well			

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

MOL & RU BOP. Released Baker Type "R" packer & pulled tubing. Ran CBL 5-1-76: & casing inspection logs. WIH with tubing & cement retainer, set retainer at 7,825'. Pumped 100 sx Cl "C" cement. Shut down overnite to WOC. WIH with tubing & tagged cement plug @ 7,759' (65' plug). Came up hole with tubing to 6,970' & spotted 300 gallons acid. Perforated 6,966'-6,972' with 2 shots per foot. Set packer at 6,904', swabbed large amount of acid water with no gas show. Laid down tubing. Shut down operation. Now attempting to obtain partner's approval to P&A.

18. I hereby certify that the foregoing is true and correct							
SIGNED Goodwin	TITLE	Administrator	Prod.	Services _{DATE}	August	23,	1976
(This space for Federal or State office use)							. 7 2
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	A	WEPTERS	S 1976 OF	35		
			. 7	audVE	1		

*See Instructions on Reverse Side, GEOLOGICAL SURVE U. S. GEOLOGICAL SURVE U. S. GEOLOGICAL SURVE I 10EBS, NEW MEXICO

Marine College

.