

(SUBMIT IN TRIPLICATE)

UNITED STATES **DEPARTMENT OF THE INTERIOR** GEOLOGICAL SURVEY

Land Offic	•	Crases
	1788	UP ESOS
Lease No.	OKŁ	kkg
() A		.egozy
Unit		
	U	Lagoth

TICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WA	TER SHUT-OFF
TICE OF INTENTION TO CHANGE PLANS		OTING OR ACIDIZING
TICE OF INTENTION TO TEST WATER SHUT-OFF		ERING CASING
TICE OF INTENTION TO RE-DRILL OR REPAIR WELL		DRILLING OR REPAIR
TICE OF INTENTION TO SHOOT OR ACIDIZE	; (1)	NDONMENT.
TICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTO	RY
TICE OF INTENTION TO ABANDON WELL	1 11	
(INDICATE ABOVE BY CHECK	MARK NATURE OF REFORT, NOTICE, OR OT	HER DATA)
l No is locatedft.		from $\frac{E}{E}$ line of sec.
(7 Sec. and Sec. No.) (1 1)	(Range) (Meridian)	()
(Field)	unty or Subdivision)	E(CLASS Territory)
elevation of the derrick floor above se	ea level is accor ft.	
	301	\ _3 (* ,
50 PT		
names of and expected depths to objective sands; shing points, and		
with injection rate 20 BPK.	ow sizes, weights, and lengths of proposed dall other important proposed work) Offect. Perforated 4 at the many acid through peril and 10,000 f sand. Gauged 10,250 MCFGPD.	hots per foot from forations and SOF wi fook treatment at
will was plugged back to 313 0-3110 ft. Acidised 500 gallers Dowell Sandfrac Of With injection rate 20 BPM.	ow sizes, weights, and lengths of proposed dall other important proposed work) Consume and acid through per li and 10,000 f sand. Gauged 10,250 MCFGPD.	hots per foot from forations and SOF wi fook treatment at Absolute open flow
will was plugged back to 313 0-3110 ft. Acidised 500 gallers Of with injection rate 20 BPM.	ow sizes, weights, and lengths of proposed dall other important proposed work) Consume and acid through per li and 10,000 f sand. Gauged 10,250 MCFGPD.	hots per foot from forations and SOF wi fook treatment at Absolute open flow
will was plugged back to 313 0-3110 ft. Acidised 500 galls 000 gallons Dowell Sandfrac Oi 00 with injection rate 20 BPM.	ow sizes, weights, and lengths of proposed dell other important proposed work) Of feet. Perforated 4 at the man and acid through per L1 and 10,000 / sand. Gauged 10,250 MCFGPD.	hots per foot from forations and SOF wi fook treatment at Absolute open flow
will was plugged back to 313 0-3110 ft. Acidised 500 galls 000 gallons Dowell Sandfrac Oi 00 with injection rate 20 BPM.	ow sizes, weights, and lengths of proposed dall other important proposed work) Of feet. Perforated 4 at the same and acid through per 12 and 10,000 / sand. Gauged 10,250 MCFGPD.	hots per foot from forations and SOF will fook treatment at Absolute open flow 29
will was plugged back to 313 0-3110 ft. Acidised 500 galls 0000 gallens Dowell Sandfrac Of 000 with injection rate 20 BPM. DEP 26 1055 Inderstantial transfer of work mast racing approximately approximately back Bldg.	ow sizes, weights, and lengths of proposed dall other important proposed work) Of feet. Perforated 4 at the same and acid through per 12 and 10,000 / sand. Gauged 10,250 MCFGPD.	hots per foot from forations and SOF wi fook treatment at Absolute open flow
will was plugged back to 313 0-3110 ft. Acidised 500 galls 000 gallens Dowell Sandfrac Oi Of with injection rate 20 BPM. DEP 26 1055 Address and standard work mast racing approximately and standard s	ow sizes, weights, and lengths of proposed dall other important proposed work) Of feet. Perforated 4 at the same and acid through per 12 and 10,000 / sand. Gauged 10,250 MCFGPD.	hots per foot from forations and SOF wi fook treatment at Absolute open flow 20 20 20 20 20 20 20 20 20 20 20 20 20

gradien der Steinen der Steine de

and the second of the second o

المالية المحالية المحالة المحالية المحالية المحالية المحالية المحالية المحالية المحالية المحالية المحالية المح

100 miles (100 miles 100 miles