


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



DUPLICATE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

CULBERTSON & IRWIN, INC

Box 1071, Midland, Texas

Company or Operator

GEO. W. DABBS EST.

Well No.

1

NE NW

of Sec.

35

T. 25-S

Address

R. 37-E

N. M. P. M.

Langlie

Field.

Lea

County.

Well is 330

feet south of the North line and

2970

feet west of the East line of

Section

If State land the oil and gas lease is No.

Assignment No.

If patented land the owner is

Geo. W. Dabbs Est.

Address

Las Cruces, New Mexico

If Government land the permittee is

Address

The Lessee is

Culbertson & Irwin, Inc.

Address

Midland, Texas

Drilling commenced

4-29-

19 38

Drilling was completed

8-12

19 38

Name of drilling contractor

Nat'l. Drg. & Prod. Co

Address

Midland, Texas

Elevation above sea level at top of casing

3021

feet.

The information given is to be kept confidential until

19

OIL SANDS OR ZONES

No. 1, from

3205

to

3240

No. 4, from

to

No. 2, from

to

No. 5, from

to

No. 3, from

to

No. 6, from

to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from

to

feet.

No. 2, from

550

to

560

feet.

No. 3, from

to

feet.

No. 4, from

to

feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
13"	42	8 thd	Used	4351	TP				
8-5/8	32	8 thd	Used	1198'	11" TP				
7	22	8 thd	New	2944	TP				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
18"	13	435	100	Halliburton		
10"	8-5/8	1198-11	100	"		
8"	7"	2944	150	"		

PLUGS AND ADAPTERS

Heaving plug - Material

Length

Depth Set

Adapters - Material

Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
4 1/2		Gelatine	590	Aug. 7	3225-3290	

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 3331 feet, and from feet to feet

PRODUCTION

Put to producing August 12, 1938

The production of the first 24 hours was 69 barrels of fluid of which 100 % was oil; 0 %

emulsion; 0 % water; and 0 % sediment. Gravity, B. 40° plus

If gas well, cu. ft. per 24 hours. Gallons gasoline per 1,000 cu. ft. of gas.

Rock pressure, lbs. per sq. in.

EMPLOYEES

National Drilling & Prod. Co. Driller Driller

Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 13

Midland, Texas.

Aug. 13, 1938

Place Date

August

38

Name

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
15	35	20	Caliche
35	95	40	Sand
95	858	763	Redbeds
858	1015	157	Anhydrite
1015	1025	10	Redrock
1025	1195	170	Anhy., Salt & Redrock
1195	1210	15	Anhy
1210	1225	15	Sand
1225	1250	25	Anhy & Redrock
1250	1300	50	Salt & Anhy
1300	2200	900	Salt, Anhy & Potash
2200	2305	105	Anhy
2305	2345	40	Lime (brown and gray)
2345	2385	40	Lime, Shale breaks
2385	2460	75	Broken Lime, Sand
2460	2575	15	Brown Lime & Anhy
2475	2550	55	Anhy & Redrock
2530	2670	140	Brown & Gray Lime and Anhy.
2670	2790	120	Brown & Gray Lime
2790	2865	75	Lime
2865	2945	80	Lime & Anhy
2945	3055	110	Lime
3055	3075	20	Brown Lime & Sand
3075	3095	20	Lime
3095	3105	10	Sandy Lime
3105	3120	15	Lime
3120	3195	75	Sandy Lime
3195	3205	10	Sandy Lime (S/O)
3205	3240	35	Oil sand
3240	3274	34	Lime
3274	3280	6	Sand, Lime, (broken)
3280	3331	51	Lime.

TD