

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from.....0.....feet to.....4875.....feet, and from.....feet to.....feet.
Cable tools were used from.....feet to.....feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing....., 19.....

OIL WELL: The production during the first 24 hours was..... barrels of liquid of which.....% was
was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
Gravity.....

GAS WELL: The production during the first 24 hours was..... 5600..... M.C.F. plus..... Q.....
liquid Hydrocarbon. Shut in Pressure 1900..... lbs.

Length of Time Shut in..... 24..... hours.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.....	782'	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....		T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....		T. Montoya.....	T. Farmington.....
T. Yates.....	2260'	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	2540'	T. McKee.....	T. Menefee.....
T. Queen.....	2960'	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....		T. Gr. Wash.....	T. Mancos.....
T. San Andres.....		T. Granite.....	T. Dakota.....
T. Glorieta.....		T.	T. Morrison.....
T. Drinkard.....		T.	T. Penn.....
T. Tubbs.....		T.	T.
T. Abo.....		T.	T.
T. Penn.....		T.	T.
T. Miss.....		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	11.2		Distance from Top Kelly Drive Bushing to Ground				DEVIATION - TOTCO SURVEY
	248		Caliche and Red Bed				1/2 - 300'
1033			Red Bed				1/2 - 425'
1512			Red Bed and Shells				1/2 - 800
2144			Anhydrite and Salt				1-3/4 - 1550
2640			Anhydrite and Gypsum				3 - 2140
2741			Anhydrite				3 - 2250
2801			Anhydrite and Gypsum				3 - 2290
3165			Anhydrite				2-3/4 - 2430
3339			Sandy Lime				2-3/4 - 2540
3782			Lime				2-3/4 - 2640
3937			Sandy Lime				2-3/4 - 2704
4318			Lime				2-3/4 - 2950
4342			Lime and Chert				1-1/2 - 3245
4875			Lime				1-1/4 - 3312
							1-3/4 - 3455
							1-3/4 - 3600
							2 - 4240
							1-3/4 - 4400
							2

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 10, 1957

(Date)

Company or Operator.....Gulf Oil Corporation..... Address.....Box 2167, Hobbs, New Mexico.....

Name.....B. L. Taylor..... Position.....Area Supt. of Prod.....