

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Texaco E&P Inc.

3. Address and Telephone No.

P.O. Box 3109, Midland, Texas 79702 (915) 688-4438

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit G 2310 FNL, 2310 FEL, Section 19, T-24-S, R-38-E

5. Lease Designation and Serial No
NM 0349952

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

West Dollarhide Drinkard Unit # 6

9. API Well No

30 025 12216

10. Field and Pool, or Exploratory Area

Dollarhide, Drinkard, Tubbs, Queen

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other _____
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Notify BLM of intent to plug
- 2) MIRU, NU BOP
- 3) Set CIBP @ 6250, mix and circulate 10# mud
- 4) Spot 20 sx cement fm 6150-6250 (Tubbs)
- 5) Spot 20 sx cement fm 5200-5300 (Glorieta)
- 6) Perf/Sqz 40 sx cement fm 3508-3608 (Queen)
- 7) Perf/Sqz 40 sx cement fm 3175-3275 (8 5/8 shoe) WOC/Tag
- 8) Perf/Sqz 40 sx cement fm 2660-2760 (b-salt) WOC/Tag
- 9) Perf/Sqz 40 sx cement fm 1385-1485 (t-salt) WOC/Tag
- 10) Spot 5 sx cement fm 50'
- 11) RDMO, cut off well head, install dry hole marker, clean location

**SEE ATTACHED FOR
CONDITIONS OF APPROVAL**

14. I hereby certify that the foregoing is true and correct

Signed *J. T. Calhoun*

Title Engineer

Date 12/01/99

(This space for Federal or State office use)

Approved by (ORIG. SGD.) ALEXIS C. SMOBODA

Title PETROLEUM ENGINEER

Date DEC 07 1999

Conditions of approval, if any:

