

State of New Mexico
Energy, Minerals and Natural ResourcesForm C-103
Revised March 25, 1999OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30-025-12250

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

WEST DOLLAHIDE

Drinkard

8. Well No.

17

9. Pool name or Wildcat

Drinkard, Tubb, Queen

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other Injector

2. Name of Operator

TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator

P.O. Box 730 HOBBS, NEW MEXICO 88240-2528

4. Well Location

Unit Letter C : 535 feet from the NORTH line and 2310 feet from the WEST lineSection 30 Township 24-S Range 38-E NMPM LEA County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒CASING TEST AND CEMENT JOB ☐OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. SET 5 1/2" CIBP @ 6575', CAPPED w/ 25 SX PLUG ON CIBP TOC (4" 6300')
2. DISPLACE HOLE w/ SALT GEL MUD, 9.5# BRINE w/ 25# GEL P/BSL
3. SPOT 25 SX PLUG 6222-6122 (TUBB)
4. SPOT 40 SX PLUG 3830-3540 (GRAYBURG)
5. PERF 3290', UNABLE TO PUMP INTO PERFS, SPOT 25 SX PLUG TAG @ 3135
6. PERF 2638', UNABLE TO PUMP INTO PERFS, SPOT 25 SX PLUG TAG 2484' (B-SALT)
7. PERF 1380', SQZ 40 SX 1380-1280 TAG @ 1151 (T-SALT)
8. PERF 425', SQZ 60 SX 425-325 TAG @ 282 (8 5/8 SHOE)
9. SPOT 15 SX, 30' SURFACE
10. INSTALL DRY HOLE MARKER, CLEAN LOC 3/27/00

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Poly AbalosTITLE Vice-PresidentDATE 3/27/00Type or print name POLY ABALOS(915)
Telephone No. 683-4996

(This space for State use)

APPROVED BY Tony M. HillTITLE Supervisor

DATE

Conditions of approval, if any:

GW