

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN
(Other in
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-067968

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	West Dollarhide Drinkard Unit
2. NAME OF OPERATOR SKELLY OIL COMPANY	West Dollarhide Drinkard Unit
3. ADDRESS OF OPERATOR P. O. Box 1351 Midland, Texas 79701	9. WELL NO. 29
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1650' FSL and 1980' FEL Sec. 30-24S-38E	10. FIELD AND POOL, OR WILDCAT Dollarhide Tubb-Drinkard 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 30-24S-38E
14. PERMIT NO. -----	15. ELEVATIONS (Show whether DF, RT, GR, etc.) UNKNOWN
	12. COUNTY OR PARISH LEA
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐Convert to water injection ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- (1) Moved in and rigged up workover rig Sept. 27, 1969.
- (2) Pulled rods and tubing.
- (3) Connected well to injection system and began pressuring up on Sept. 28, 1969.
- (4) Moved in and rigged up workover rig Dec. 5, 1969.
- (5) Wireline indicated fill-up at 6817'.
- (6) Ran 2-3/8" OD cement-lined tubing with Guiberson 5 1/2" x 2" packer set at 6166'.
- (7) Loaded casing annulus behind tubing with water treated with inhibitors.
- (8) Hooked well to injection system and began injecting water on Dec. 7, 1969, into perforations 6459-6545' and 6750-6810' of the Drinkard Reservoir.

This is a water injection well for the West Dollarhide Drinkard Unit operated by Skelly Oil Company

18. I hereby certify that the foregoing is true and correct
(Signed) J. R. Avent

SIGNED

J. R. Avent

TITLE

District Office Manager

DATE

December 10, 1969

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DEC 12 1969

*See Instructions on Reverse Side

GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847-485