

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
1. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Unit Letter I, 1650' FSL & 510' FEL Sec. 30-24S-38E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3176' DF

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

West Dollarhide Queen Sand Unit

8. FARM OR LEASE NAME

West Dollarhide Queen Sand Unit

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30-24S-38E

12. COUNTY OR PARISH 13. STATE

Lea

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) Move in workover rig. Pull rods and tubing.
- 2) Set Cast Iron Bridge Plug at +3500' with 25 sacks cement on top.
- 3) Set 25 sack cement plug 2600-2800'.
- 4) Set 100 sacks cement plug at 1100-1300'.
- 5) Set 10 sack cement plug to surface.
- 6) Install dry hole marker.

All strings of casing will be left in the hole. All intervals not cemented will be filled with 10.2# mud.

18. I hereby certify that the foregoing is true and correct

SIGNED LELAND FRANZ

TITLE Dist. Production Manager

DATE 2-23-77

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED
AS AMENDED

MAR 2 1977

BERNARD MOROZ

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

