

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

M. Oil Cons. Division  
1625 N. French Dr.  
Hobbs, NM 88240

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

Injector

2. Name of Operator

TEXACO Exploration & Production Inc

3. Address and Telephone No.

P.O. Box 3109 Midland, TX 79702 (915) 688-4438

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

UNIT LETTER A, 990 FEET FNL, 990 FEET FEL  
SECTION 30, TOWNSHIP 24-S, RANGE 38-E

5. Lease Designation and Serial No.

0349952 - NM

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. WEST

DOLLARHIDE DRINKARD #15

9. API Well No.

30-025-12264

10. Field and Pool, or Exploratory Area

DOLLARHIDE, DRINKARD  
TUBBS, QUEEN

11. County or Parish, State

LEA NEW MEXICO

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☒ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. WELL HAD 3 BPM FLOW, SQZ 50 SXs UNDER PKR WOC TAG @ 6550' OK'D SQUEEZE BY 13HM
2. DISPLACE HOLE w/ SALT GEL MUD 9.5# BRINE w/ 25# GEL P/BBL.
3. SPOT 30 SX PLUG 4" LINDER 6550'-6200' (DRINKARD - TUBBS) COMBINE
4. SPOT 20 SX PLUG 4" LINDER 5400'-5300' (GLORIETA)
5. SPOT 20 SX PLUG 4" LINDER 3900'-3800' (QUEEN)
6. PERF @ 3250', UNABLE TO PUMP INTO PERFS, SPOT 25 SX PLUG 3250'-3000' (8 5/8 SHOE) TAG @ 2944'
7. PERF @ 2825', UNABLE TO PUMP INTO PERFS, SPOT 25 SX PLUG 2825'-2700' (B-SALT)
8. PERF @ 1590', UNABLE TO PUMP INTO PERFS, SPOT 25 SX PLUG 1590'-1490' (TOP-SALT) TAG @ 1440'
9. PERF @ 355', SQZ 70 SXs 355'-255' 8 5/8 CSG (13 3/8 SHOE) TAG 85'
10. 15 SX PLUG 60-SURF, INSTALL DRY HOLE MARKER 5/16/00

14. I hereby certify that the foregoing is true and correct

Signed

Gary Gourley

Title

VICE-PRESIDENT (915) 683-4996

Date

5/16/00

(This space for Federal or State office use)

(ORIG. SGD.) GARY GOURLEY

Title

PETROLEUM ENGINEER

Date

JUN 15 2000

Conditions of approval, if any: