

Orig:acc: OCC

cc: VDA

JTR

F

(Form C-103)
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION Plug back	x	REPORT ON (Other) Acid treatment	x

July 18, 1953

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company

(Company or Operator)

Leslie E. Vance

(Lease)

Capitan Drilling Company

(Contractor)

Well No. **2** in the **NE** $\frac{1}{4}$ **SW** $\frac{1}{4}$ of Sec. **30**T. **24 S**, R. **38 E**, NMPM., **Dollarhide-Drinkard** Pool, **Lea** County.

The Dates of this work were as follows:

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD - 7,000' - Drilled to 7,000' - Took DST, recovered 140' Mud and 140' salt water.
Spotted cement plug 7,000 to 6838' - Set 5 1/2" casing @ 6837' and cemented with 450 sacks.

Ran tubing W/bit and drilled cement to 6808'

Perforated 5 1/2" casing 6470 to 6570 with 400 - 1/2" jet shots. Treated w/1,000 gallons of mud acid. No show of oil or gas.

Acidized w/2,000 gallons of 15% regular acid. recovered load and 28 Bbl. of new oil

Acidized w/5,000 gallons of 15% regular acid. recovered load and 99 Bbl. of new oil

Acidized w/10,000 gallons of 15% regular acid. recovered 101 Bbl. of new oil first 24 hours, 47 Bbl. of new oil, 2nd 24 hours, lost swab and pulled tubing to recover swab.

Swabbed & flowed 3rd 24 hours, 91 Bbl. of new oil. Took potential test of 38 Bbl. flowing thru open 2" tubing in 4 hours.

Witnessed by **Robert E. Siverson**
(Name)**Sinclair Oil & Gas Company**
(Company)**Dist. Engineer**
(Title)

Approved:

OIL CONSERVATION COMMISSION

Roy Yankovich
(Name)
Oil & Gas Inspector
(Title)

JUL 20 1953

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name *Leslie E. Vance*Position **Dist. Supt.**Representing **Sinclair Oil & Gas Co.**Address **Box 1927 Hobbs, New Mexico**