

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instruction
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC - 069052

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Elliott H. Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Dollarhide-Devonian

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

31-24-38

12. COUNTY OR PARISH 13. STATE

Lea

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

HNG Oil Company

3. ADDRESS OF OPERATOR

c/o Hobbs Pipe & Supply Co., Box 2010, Hobbs, N. M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980 FNL & 660 FEL, S-31, R-24S, T-38E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3144'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

1. Spot a 25 sx plug across existing perforations, 7574'-7594'.
2. Spot a 100' plug at 5½" casing stub, approximately 4,000'.
3. Spot a 100' plug in and out of the base of 9-5/8" casing at 3195'.
4. Spot a 15 sx plug in the surface and set a 4" regulation marker.
5. Hole will be loaded with mud-laden fluids.

AMENDMENT:

Place additional 25 sack cement plug inside 9-5/8" casing at 1100-1200 feet.
Hole to be filled with mud between plugs.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 12/5/72

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

DEC 11 1972