

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPI  
(Other instructions  
verse side)

TE  
re

Form approved.  
Budget Bureau No. 1004-113  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-069052

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Water injection well

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR  
Sirgo-Collier, Inc.

P. O. Box 3531, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

Unit A, 660' FNL 660' FEL, Sec. 31, T24S, R38E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3151' KB

7. UNIT AGREEMENT NAME

West Dollarhide Queen

8. FARM OR LEASE NAME

9. WELL NO.

25

10. FIELD AND POOL, OR WILDCAT

Dollarhide Queen

11. SEC., T., R., M., OR BLE. AND  
SURVEY OR AREA

Sec. 31, T24S, R38E

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Cement 4-1/2" casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1-23-88

Deepen to TD of 3890'. Ran 124 joints of 4-1/2" 10.5# casing to 3884'.  
Cemented with 300 sx Halliburton Light with 1/4# flocele and 0.5% CFR-2,  
tailed with 200 sx Class "C" with 10# Microbond and 0.2% Halad-4.  
Circulated 75 sx.

18. I hereby certify that the foregoing is true and correct

SIGNED Amy L. Whitley

TITLE Agent

DATE March 2, 1988

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

\*See Instructions on Reverse Side

SSS