


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 069052
Unit _____



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	☒	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 25, 1953

Well No. 5 is located 300 ft. from N line and 1650 ft. from E line of sec. 31

NE 1/4 sec. 31 (1/4 Sec. and Sec. No.) 24S (Twp.) 30E (Range) R. M. F. M. (Meridian)

West Dallardide (Queen) (Field) Lee (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill a 13-3/4" hole to depth of approximately 215 feet and cement 10-3/4" 40.75# casing on bottom with sufficient cement to circulate back into cellar. We will drill an 8-3/4" hole; below surface casing, to a depth of approximately 3650 feet and cement 7" casing on bottom with an estimated amount of cement sufficient to bring returns back to base of surface casing.

We will allow cement time of 24 hours on surface casing and 72 hours on pay string. All cement jobs will be tested in conformity with Federal regulations.

Estimated total depth of hole is 3750 feet.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company L. E. Elliott

Address Demwell, New Mexico

By _____

Title Agent

WRS COMPLETION REPORT

COMPLETIONS
PI# 30-T-0023 05/02/88

SEC 31 TWP 24S RGE 38E
30-025-12276-0001 PAGE 1

NMEX LEA * 330FNL 1650FEL SEC NW NE
STATE COUNTY FOOTAGE
SIRGO-COLLIER INC IWD IW
OPERATOR
WI-24 WEST DOLLARHIDE (QUEEN SAND) UNIT
WELL NO. LEASE NAME
3138DF DOLLARHIDE
OPER ELEV FIELD POOL AREA
API 30-025-12276-0001

LEASE TYPE NO. PERMIT OR WELL I.D. NO. STATUS
01/13/1988 02/15/1988 ROTARY
SPUD DATE COMP. DATE TYPE TOOL
3936 QUEEN NOT RPTD
PROJ. DEPTH PROJ. FORM CONTRACTOR
DTD 3890 OTD 3750 FM/TD QUEEN
DRILLERS T.D. LOG T.D. PLUG BACK TO OLD T.D. FORM T.D.

6 MI NE JAL, NM

CASING/LINER DATA

CSG 4 1/2 @ 3890 W/ 500 SACKS

TUBING DATA

TBG 2 3/8 AT 3473

PRODUCTION TEST DATA

QUEEN PERF 3588- 3626 3662- 3726 3588- 3726 GROSS
PERF 3588- 3626 8000GALS
ACID 3588- 3726
15% NEFE

LOGS AND SURVEYS /INTERVAL, TYPE/

LOGS CNL CBL

DRILLING PROGRESS DETAILS

SIRGO-COLLIER INC
BOX 3531
MIDLAND, TX 79702
915-684-7757
OWDD: OLD INFO: FORMERLY SKELLY OIL #24
WEST DOLLARHIDE (QUEEN SAND) UNIT. ELEV

CONTINUED IC# 300257000588

Petroleum Information

Copyrighted 1985
Petroleum
Information Corporation

DB a company of
The Dun & Bradstreet Corporation

WRS-GET
Form No. 167

COMPLETIONS
PI# 30-T-0023 05/02/88 SEC 31 TWP 24S RGE 38E
30-025-12276-0001 PAGE 2

SIRGO-COLLIER INC
WI-24 WEST DOLLARHIDE (QUEEN SAND) UNIT IWD IW

DRILLING PROGRESS DETAILS

3138 DF. SPUD 5/25/53. 10 3/4 @ 198 W/180 SX,
7 @ 3638 W/800 SX. LOG TOPS: YATES 2685,
QUEEN 3280, PENROSE 3580. OTD 3750. COMP
6/12/63. IPF 389 BOPD. PROD ZONE: QUEEN
3638-3750 (OH).
ABANDON LOCATION ISSUED 02/21/83
WATER INJECTION WELL
FORMERLY ABND LOC BY GETTY OIL UNDER
API 30-025-12276-0001 & IC 30-025-70477-81
LOC/1988/
01/04 DEEPENED 3750 TO 3890
04/25 RAN 4 1/2 CSG
04/25 3890 TD
COMP 2/15/88, WIW
INJ ZONE - QUEEN 3588-3726
NO CORES OR DSTS RPTD